

HALE

TRAILER

BRAKE & WHEEL



A034050-A034052
VIN: A7276-A7278

SALES | RENTALS | PARTS | SERVICE

| | |
|---------------------------------------|--------------------------------------|
| Allentown, PA: 800-383-8894 | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Raleigh, NC: 833-418-9777 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310 |

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

| Magnitude 55L Plus Air Tridem (Flat Level Deck) (Model: MAGNITUDE 55L Plus) | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| MAG55LP**F*826543 | |
| | Est. Wt.: 23,810# +/- 3% |
| TRAILER - GENERAL | |
| Capacity: 55 tons in 10-foot length with 4 axles close coupled; 55 tons in 16-foot length with single axle spreader - GAWR and GVWR determine legal payloads | |
| Length: 52 feet 3 inches (with standard deck length and axle spread) | |
| Compatibility: Designed to accept 55/60 rear axle below, spreader and/or 35 inch flipbox - none | |
| Accent Package: None | |
| GOOSENECK | |
| Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 11in overall gooseneck length) set up for wetline operation | |
| Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal) | |
| Swing Radius: 102 inches (11 feet 11 inches overall gooseneck length) | |
| Kingpin: Removable kingpin at 102 inch radius | |
| Power Source: Set up for wet line operation | |
| VIN Plate: Bilingual VIN plate | |
| Registration/Document Holder: Registration/document holder installed | |
| Hydraulic Fittings: OEM Standard 1/2 inch | |
| DECK | |
| Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs | |
| Deck Width: 8 feet 6 inches overall (unless optional deck width is selected) | |
| Deck Length: Flat Level Deck (FLD) design - standard 26 feet clear deck length - Standard OAL 52 feet 3 inches | |
| Loaded Deck Height: 18 inches with 6 inches ground clearance | |
| Crossmembers: On 24 inch centers (nominal) | |
| Chain Slots: Chain Slots located on siderail | |
| Front Ramps: Manual front approach ramps included | |
| Front Bogie Ramp: Included as standard | |
| Extension Brackets: 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck) | |
| Flooring: 2 inch nominal wood - side rails only | |
| Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers | |
| Hammer Plate: None | |
| REAR BRIDGE | |
| Front Bogie Ramp: Included as standard | |
| Boom Trough: Low Boom Well V crossmembers with bolt-in V pan | |
| Deck to Bogie Connection: Fixed | |
| Bolsters: Recessed load bearing between all axles and rear of last axle | |
| Covered Rear Bogie: None | |
| Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters | |
| Bumper: Heavy duty V-style rear bumper | |
| AXLES | |
| Number of Axles: 3 axles | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |

| | |
|------------------------------------------------------------------------------------------------------------------------------|--|
| Axle Spread: 54.5 inches (between axles) | |
| Dust Shields: None | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Spring Brakes: None | |
| SUSPENSION | |
| Suspension: Air ride | |
| ABS: None required | |
| Chain Lift: First Axle (acts as limit chains) | |
| Override Chains: Override Chains Axle 2 & 3 | |
| Third Axle Lift: Air lift | |
| Mechanical Ride Height Control: 7-position mechanical ride height control system | |
| Manual Dump Valve: Manual Dump Valve (Push Pull) | |
| Liquid Filled Gauge: Liquid filled air gauge installed | |
| Load Scale: None Standard | |
| WHEELS AND TIRES | |
| Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted | |
| Tires: 275/70R 22.5 OEM standard | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| LIGHTING | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes | |
| Tail Lights: 3 tail light package | |
| Electrical Receptacle: J560 7-pin connector | |
| Marker Lights: 3 marker lights per side including mid turn | |
| Additional Marker Lights: None Standard | |
| PAINT | |
| Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001 | |
| MISCELLANEOUS | |
| Lash Rings: 19 pair - 38 total (when 26ft deck is selected) | |
| Flag Holders: 2 pair | |
| AVAILABLE COMPONENTS | |
| Flipbox: None included | |
| Flip Axle: None standard | |
| Hydraulic Flip Axle Option: None Standard | |
| Dust Shields on Flip Axle: None standard | |
| Spreader: None | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.