



A034126-A034140

VIN: A7189-A7203

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Renegade XN20 Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE XN20)

RENLXT40NF*834542

Est. Wt.: 24,810# +/- 3%

TRAILER - GENERAL**Capacity:** 40 tons in 16-foot length - GAWR and GVWR determine legal loads**Load Base:** 16-foot rigid 2-point load centered in deck when deck is fully closed.

Note: Only rigid self supporting loads when deck is open. The load base becomes the open deck minus 2ft.

Length (Trailer Only): 50 feet 1 inch (closed); 71 feet 1 inch (open)**Width:** 8 feet 6 inches**Compatibility:** Designed to accept optional third flip axle**GOOSENECK****Gooseneck Design:** Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation**Loaded Fifth Wheel Height:** Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)**Power Source:** None**DECK****Deck Design:** Flat level telescopic deck design**Deck Length:** 34 feet 0 inches clear deck length (retracted) - 60 feet 0 inches (extended) **Note when option is selected trailer overall length is 55 ft 1 in**Loaded Deck Height:** 20 inches with 6 inches ground clearance**Flooring:** 1 3/8 inch nominal wood (full width)**Recessed Floor Mounted D-Ring Package:** None**Crossmembers:** On 24 inch centers**Front Ramps:** None, front of deck sloped top down to assist in loading with traction cleats**Extension Brackets:** Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type**Front Bogie Ramp:** Sloped steel bogie ramp (full width)**Deck to Bogie Connection:** Fixed**AXLES****Number of Axles:** 2**Axle Capacity:** 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.**Axle Spread:** 54.5 inches spread (between axles)**Brakes:** 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount**Dust Shields:** None**Spring Brakes:** Spring brakes on 2 axles**SUSPENSION****Framework:** All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs**Suspension:** Air ride with automatic controls**First Axle Lift:** Chain lift included on first axle when 34ft deck is selected**ABS:** 4S/2M system without diagnostic tool and cable**Load Scale:** None Standard**WHEELS AND TIRES****Wheels:** 8.25 x 22.5 Lvl One buffed outside/steel inside - hub-piloted

Tires: 255/70R 22.5 H ply OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
REAR BRIDGE	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 41 inches	
Bumper: 3 tail light package	
Mini Boom Trough & Traction Cleats: None	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Liquid Filled Gauge: Included	
Accent Package: Stainless steel bumper insert	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 8 marker lights per side including mid-turn	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 12 pair - 24 total	
Flag Holders: 2 pair flag holders	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	
AVAILABLE COMPONENTS	
Flip Axle: None	
Dust Shields on Flip Axle: None	
Additional Options:	
Tire Inflation System Prepped Only	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.