

HALE

TRAILER

BRAKE & WHEEL



A034166-A034170
VIN: 392266-392270

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

BODY

REGION (1) DOMESTIC
LOAD PROFILE (1) 72K
VESSEL THICKNESS (1) 0.190 5454-H32 ALUMINUM
CUBIC FT CAPACITY (1) 1050
COMMODITY (1) SAND
MODEL SUB TYPE NONE
TRAILER OPERATION TYPE (1) PNEUMATIC
FOOD GRADE NONE
VESSEL FINISH (1) MILLED
LENGTH (1) 42 FT. / 12.80 M.
WIDTH (1) 96
OPERATING TEMPERATURE (1) 185 F / 85 C
OPERATING PRESSURE (1) 14.7 PSI / 101.35 KPA
COMPARTMENT OPTIONS (1) SINGLE COMPARTMENT
LOWER HOPPER CONES (1) WELD-ON 45 DEG (STANDARD)
MANLID QUANTITY (1) 3
MANLID LOCATION LAYOUT (1) OVER EACH HOPPER
FIRST MANLID TYPE (1) KNAPPCO 20IN. ALUMINUM MANLID
SECOND MANLID TYPE (1) KNAPPCO 20IN. ALUMINUM MANLID
THIRD MANLID TYPE (1) KNAPPCO 20IN. ALUMINUM MANLID

LOAD LINE

LOAD LINE QTY NONE
LOAD LINE LOCATION #1 NONE
LOAD LINE LOCATION #2 NONE

AERATION

AERATOR FORMAT (1) 3 PER HOPPER (STANDARD)
AERATOR TYPE (1) BTI SPIN FLOW AERATION KIT W/ WEAR PLATES AND 2 IN. BTI BLACKMAXX
INDIVIDUAL AERATION CONTROLS AT EACH HOPPER
AERATION LOCATION (1) DRIVER SIDE
AERATOR LINE CONTROL (1) 3" BTI BLACKMAX BUTTERFLY VALVE
AERATOR SEAT (1) WHITE RUBBER (FOOD GRADE) SEAT
AERATOR DISK (1) ALLOMAXX DISC
AERATOR HANDLE TYPE (1) ALUMINUM
AERATOR HANDLE POSITION (1) MANUAL 10 - POSITION

AIR INLET

AIR INLET SIZE (1) 3 IN. SCH. 10 ALUMINUM PIPE
TEATHER DUST CAP ON INLET
AIR INLET LOCATION (1) DRIVER SIDE
CHECK VALVES (1) (2) BTI OPTIMA CHECK VALVES - (1) AT AIR INLET & (1) UP STREAM OF FRONT

PROP / PRES CONTROL VALVE

CONTROL VALVE HOUSING (1) 3" BTI BLACKMAX BUTTERFLY VALVE

PROP / PRES CONTROL VALVE

CONTROL VALVE DISK (1) ALLOMAXX DISC

CONTROL VALVE HANDLE TYPE (1) ALUMINUM

CONTROL VALVE HANDLE POSITION (1) MANUAL 10 - POSITION

BLOW DOWN LINE

BLOW DOWN LINE HOUSING (1) 3" BTI BLACKMAX BUTTERFLY VALVE

BLOW DOWN LINE

BLOW DOWN LINE DISK (1) ALLOMAXX DISC

BLOW DOWN LINE SEAT (1) WHITE RUBBER (FOOD GRADE) SEAT

BLOW DOWN LINE HANDLE TYPE (1) ALUMINUM

BLOW DOWN LINE LOCATION (1) DRIVER SIDE FRONT

DRIVER SIDE REAR

BLOW DOWN LINE HANDLE POSITION (1) MANUAL 10 - POSITION

BLOW DOWN RELIEF PRESSURE (1) 15 P.S.I.

TOP AIR

TOP AIR VALVE HOUSING (1) 3" BTI BLACKMAX BUTTERFLY VALVE

TOP LINE LOCATION (1) DRIVER SIDE FRONT

PRODUCT & DISCHARGE

PRODUCT / DISCHARGE LINE SIZE (1) 4 IN

PRODUCT / DISCHARGE LINE MATERIAL (1) STEEL

PRODUCT / LINE MATERIAL GAUGE SCHD.40

PRODUCT VALVE SIZE (1) 5" BTI BLACKMAXX BUTTERFLY VALVES

PRODUCT VALVE SEAT (1) WHITE RUBBER (FOOD GRADE) SEAT

PRODUCT VALVE DISK (1) ALLOMAXX DISC

PRODUCT LINE CONNECTIONS FR & RR (1) BTI VICTAULIC COUPLERS -BOLT ON

PRODUCT/DISCHARGE LINE CONNECTION (1) MAC Rubber Sleeves with Stainless Worm Gear Clamp

PRODUCT VALVE HANDLE TYPE (1) ALUMINUM

PRODUCT VALVE HANDLE POSITION (1) MANUAL 5 - POSITION

PRODUCT TEE TYPE (3) 5 X 4 BTI SANDHOG STEEL BOTTOM DROP TEE

REAR DISCHARGE LOCATION (1) EXTEND THROUGH AXLES TO REAR

NO. OF GAUGE ENCLOSURE (1) 1

GAUGE LOCATION (1) Driver Side -Rear- Forward of Tandem

LIGHTS

LIGHT TYPE (1) GROTE L.E.D. W/ GROMMET

REAR I.D. LIGHTS (1) (3) I.D. LIGHTS TOP

3 PENNY LIGHTS ADDED TO SECOND RUNG FROM BOTTOM

LIGHT PANEL (1) (TURN) (STOP) (STOP) - (STOP) (STOP) (TURN)

STD. MARKER LIGHTS (1) 2 EACH SIDE FRONT & REAR

MID-TURNS (1) (2 PAIR) LED-BOXED IN

3 PENNY LIGHTS AS MID TURNS PER SIDE

BACK-UP LIGHTS NONE

BACK-UP LIGHT LOCATION NONE

BACK UP LIGHT CONTROLS NONE

AUXILIARY CABLE NONE

NO. OF WORK LIGHTS (2) 2

WORK LIGHT MODEL (1) L.E.D. CUBE WORK LIGHTS

WORK LIGHT LOCATION (1) (2) DRIVER SIDE FRONT FENDER

WORK LIGHT SWITCH LOCATION (1) OUTSIDE

PRIMARY AXLES

MODEL (1) TANDEM
NO. OF PRIMARY AXLES (2) 2
SUSPENSION (2) HEND. INTRAAX AAT W/ RAISED AXLE - TP SPINDLE
NO. OF LIFT KITS 0
AXLES (1) 71.5" AXLES
LIFT KIT_ NONE
LIFT CONTROLS NONE
WHEEL END PACKAGE (1) YES (HXL5)
BRAKES (2) 7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS (1) HEND. INTRAAX
HUB AND DRUM (2) CENT W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.
TIRES (8) GENERAL RA 11 R 22.5 16 PLY
WHEELS (8) ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
PRIMARY AXLE TIRE INFLATION SYSTEM NONE

CHASSIS

5TH WHEEL PLATE (1) BLACK POWDER COATED STEEL, ADJUSTABLE
5TH WHEEL PLATE HEIGHT (1) 48 IN. HIGH
SUSPENSION CONTROL (1) AUTOMATIC DUMP ON EMERGENCY GLADHAND
SCALE SYSTEM (1) LOAD GAUGE - DRIVER SIDE REAR
ABS FOR TRAILER (1) (1) 4S2M MERITOR / WABCO
SLACKS (1) AUTO
HUBODOMETER_ NONE
DOLLIES - LANDING GEAR - LANDING LEGS (1) JOST - 5 YEAR NO LUBE- D.S.
HOLLAND HARK V LANDING GEAR - DS CRANK
AIR TANKS (1) ALUMINUM TANK

PAINT

SUSPENSION COLOR (1) MAC BLACK
MAC MACHINE FINISH LOGOS (1) BLACK (931716)

ACCESSORIES

FOLDING LADDER RAIL NONE
BOLT ON TOW HOOK
FOLDING LADDER RAIL OPERATION TYPE NONE
TOE RAIL (1) FULL LENGTH ON BOTH SIDES
CABINET NONE
CENTER WALKWAY (1) ADHESIVE BACKED, SKID-RESISTANT TAPE BETWEEN TOE RAILS
HOSE STORAGE TUBE (1) (2) 8 IN. x 21 FT. ALUM HOSE TUBES OUTBOARD 1 PER SIDE & (2) 8 FT. x 10 FT. 6 IN ALUM HOSE TUBES INBOARD 1 PER SIDE
GAUGES (1) 1 - LINE P.S.I. / 1 TANK P.S.I. - (INSIDE ILLUMINATED ENCLOSURE)
MUD FLAPS (1) ANTI-SAIL FLAPS (REAR OF FRONT FENDERS AND REAR OF BACK FENDERS)
PRODUCT DISCHARGE HOSE NONE
FENDERS_ (1) ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR
DOCUMENT HOLDER (1) LOCATED DRIVER SIDE NEAR LANDING GEAR
AIR INLET ACCESSORIES (1) PTO HOSE HOLDER, MAST, HOOK AND DUMMY ADAPTER LOCATED DRIVER SIDE ABOVE FRONT FENDER

ACCESSORIES

TOW PLATE (1) BETWEEN FRAME RAILS AT REAR OF TRAILER

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.