

HALE TRAILER BRAKE & WHEEL

A034287-A034291
VIN: S033066-S033070

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 55 MFG: Mini-Deck

OVERALL LENGTH	53'
OVERALL WIDTH	102"
CAPACITY	55,000 LB DISTRIBUTED
WEIGHT +/- 3%	0,000 LB
GOOSENECK	
LENGTH	9' 6" FULL-WIDTH NECK
KINGPIN SETTING	16"
SWING CLEARANCE	78"
5TH WHEEL HEIGHT	50" - CUSTOMER TO CONFIRM
	SHIMMABLE NECK - SHIMS INCLUDED
	QUICK COUPLER ON FRONT OF MAIN DECK
	GLAD HANDS ON THE SIDE OF THE UPPER DECK
	WELD HOSE CAGE TO SIDE OF GOOSENECK
DECKING	1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
CHAIN SLOTS	(5) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES
D-RINGS	NO BENT PER SIDE
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
MUD FLAPS	ALUMINUM MUD FLAPS SET FORWARD
TOOLBOX	TOOLBOX AT REAR OF GOOSENECK WITH CHAIN RACK, NO LIGHT
MAIN DECK	
	(3) BEAM DESIGN
	RADIUS PER ENGINEERING
LENGTH	34' 11" (33' 11" CLEAR)
LOADED DECK HEIGHT	12" W 4" GROUND CLEARANCE
DECKING	1/4" WEAR PLATE FULL LENGTH ON BEAMS
	STEEL DECKING BETWEEN MAIN BEAMS WITH DURBAK
	1 3/8" APITONG DECKING, RAISED BETWEEN MAIN BEAMS AND OUTER BEAMS
CROSSMEMBER	(3) TUBES ON OUTSIDES OF MAIN BEAM (ADDS ABOUT 730 LBS.)
BEAMS	4" JR. I-BEAM ON 18" CENTERS
TIE DOWNS	(3) 8" FAB BEAMS
CHAIN DROPS	3/8" STIFFENERS ON 18" CENTERS WITH 1/2" X 2 1/2" BAR UNDER FLANGE
OUTRIGGERS	CHAIN DROPS ON 18" CENTERS - NO LIGHTS BELOW
RAMPS	NONE
	TAPERS TO 4"
	HOSE CAGE PLATE ON MAIN DECK
REAR DECK	
LENGTH	8' 7"
LOADED DECK HEIGHT	42" - SET RIDE HEIGHT 2" HIGHER THAN STANDARD
AXLES	(2) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	49"
ABS	4S2M WITH SPRING BRAKES ON (2) AXLES
TIRES	255 / 70R / 22.5 (H)
WHEELS	8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, MILLED ALUMINUM INSIDE DISC
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3L+5L+3L) DUAL INTENSITY TAIL LIGHT ALUMINUM PACKAGE
	4" AMBER STROBE IN THE 4TH AND 8TH POSITION. 4" TURN AND MARKER IN 1ST AND 11TH POSITION
	4" STOP AND MARKER LIGHTS IN THE 2ND, 3RD, 5TH, 6TH, 7TH, 9TH, AND 10TH POSITION

DECKING	1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
D-RINGS	(0) BENT D-RINGS PER SIDE
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL
PAINT	BLACK ZINC RICH PRIMER
ADDITIONAL	TRIPLE DONUT FRONT CONNECTOR PLATE, WELD INDICATORS NUMBERS ON THE HOLES MANUAL RIDE HEIGHT CONTROL NO AXLE STOPS (9) TOTAL TRUCKLITE LIGHTS AND CONNECTORS (2) ON UPPER DECK, (4) ON MAIN DECK AND (2) ON REAR DECK (REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS LIGHTS AND WIRING ABOVE CROSSMEMBERS CLOSE FRONT TROUGH SECTION UNDER GOOSENECK BETWEEN MAIN BEAMS W/ DRAIN HOLES NYLON LIMIT STRAPS RAISE AND LOWER VALVE GREASE HUBS IN LIEU OF OIL ADD FORMED 3/8" PLATE TO FRONT 6" OF MAIN DECK TO DEFLECT DECK OVER OBSTACLES SPACE OUT STIFFENERS ON THE MAIN DECK WITH THE CHAIN DROPS, ADD A STIFFENER AT THE REAR OF THE MAIN DECK (2) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES IN WHEEL AREA (1) SINGLE CHAIN SLOT AT REAR OF WHEEL AREA NEAR ABS LIGHT (4) SINGLE CHAIN DROPS IN CENTER OF TRANSITION OF THE WHEEL AREA LIQUID FILLED AIR GAUGE 4-WAY AT REAR

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.