

HALE

TRAILER

BRAKE & WHEEL

A034539-A034544
VIN: S033314-S033319



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TAG-ALONG
DIMENSIONS	#237901
LENGTH	36'-0" overall, 24'-0" for the floor.
WIDTH	102", full width side rail to side rail.
HEIGHT	Floor at 35" high (235/75 R17.5 tires)
COUPLING	
COUPLER PLATE	Pole with draw bar.
KING PIN LOCATION	Eye hook must be adjustable between 19 3/4" & 31" high. (2 1/4" between each adjustment holes)
STRUCTURE	**CAMBER: 3/4"***
FLANGES	3/8" x 4", 100 000 psi steel.
WEB	3/16", 80 000 psi steel. 16" high.
GOOSENECK	16" high X 78" long (at center of the draw bar).
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre.
FLOOR	Apitong or equivalent, 1 5/16" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
R	**NOTE** Bolt on checker plate option for middle section of deck. (from beavertail forward to the middle fender section.)
SIDE RAILS	Formed channel 7" @ 9.8 lbs/ft.
SIDE BOXES	None.
RUB RAILS	None.
X BRACES	Between main beams, full length.
FENDERS	Over tires at rear and at rear floor, **anti-skid plate 1/4"***.
ENDS	
FRONT RAIL	3/16" formed steel.
HEADBOARD	**15"*** high, steel.
REAR RAMP	Loading ramp to load vehicles. 1 5/16" Apitong floor.
PNEUMATIC RAMPS	(2) non sliding pneumatic ramps, **40"*** wide x 72" long. 1 5/16" Apitong floor. Locked in vertical position when not in use. (add a pin to secure the ramps control box)
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, (tail lights with male pins #53962, markers Micro-Nova #49332, 49333, (2) licence light #60280-M).
TURN SIGNAL	Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way. (for strobe light)
MAIN SYSTEM	One junction box installed at rear with special double harness. ("Manac Plus" equivalent system)
ALARM (PNEUMATIC RAMPS)	Model Grote #73250, with activation switch installed just beside the switch of the activation of the ramps.



ITEM	DESCRIPTION
SWING OUT LIGHTS	Add the sticker 303-8767 in the box above the switch of the alarm. (4) lights "SWING ARM" foldable on sides, BUILT & INSTALLED BY MANAC. **LIGHTS (L.E.D.) INCLUDED****(12'-6" total width when the swing arms are wide opened) **adjust the length of the arms consequently**. **NOTE** CONNECT AS SPECIFICATIONS REQUIRED BY MANAC WESTERN** **MAKE SURE SWING OUT LIGHTS ARE GREASABLE**
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115), with mounting plate. 10" x 11 1/2". Road side.
BOGIE BOGIE SUSPENSION U-BOLTS LIFT SUSPENSION SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS SPACERS TIRES	Fixed. Hutch H-9700, tandem, underslung, undermount, 49" spread. With nuts at bottom. Hendrickson HT-250US (6.5) (front shock) with Hendrickson SBL lift suspension. Located at 49" front of tandem. Controlled manually. 3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity, and air bags. Hendrickson, HN-S505, 25 000 lbs. capacity. (12 1/4" brakes) Welded. 28 splines. 77 1/2". None. 12 1/4", H20HXS lining. HM 218248 and HM 212049. Haldex, automatic, 28 splines, curved (6"). Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 year warranty on parts only) Webb, 8 stud disc hubs, drums 89 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. Alcoa, aluminum, "LvL ONE" finish and half made of steel, 17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts. Wheel guard 10 holes. Located between two wheels. Continental, 235/75 R 17.5 HTR-2 16 ply (31.4")
AIR SYSTEM GLAD HANDS AIR VALVES CONTROL BOX AIR TANK EXTRA AIR TANK R	At front. (with filter) Meritor Wabco, ABS, 2 sensors 1 modulator. Stainless steel. (drawing of location) Add one aluminum air tank (3100 PO/CU) to operate the ramps. **NOTE** Air line on each side of gooseneck (ilo of both lines on same side)

