

  A034634-A034636 VIN: 66336-66338	SALES RENTALS PARTS SERVICE			
	Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Concord, NC: 800-438-2250 Delmar, DE: 866-486-1400 Des Moines, IA: 888-673-5011 Elkton, MD: 800-544-7127 Jacksonville, FL: 800-828-3055	Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Raleigh, NC: 833-418-9777 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 Walpole, MA: 800-854-5310	haletrailer.com @haletrailer     	
800-232-6535 *FINANCING AVAILABLE				

We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 15.1 Units

STANDARD SPECIFICATIONS: CTSSF-45 (South Specs) **(2027 Model)**

- Type: Peerless dual axle, transport semi-trailer, **45 degree front**
- Design: Box design, flat floor, end dump, live floor
- Construction: **Skin stressed .063 natural aluminum with aluminum exterior posts (14.5" centers), skins to extend to bottom of lower rail**
- Unloading Time: Approximately 8 minutes
- Capacity: 15.1 units (112.2 cu yd)
- Dimensions: **45' long, 102" wide, 12'6" high**, 37" king pin location, 36" rear axle from rear of trailer
- Tires: Eight (8) **11:00 x 24.5 radial tires**
- Wheels: Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile **steel, Unimount**
- Axles: 22,500# cap. , 71 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks
- Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system
- A.B.S.: 2 sensor - 1 module
- Suspension: Four spring three leaf tandem (**Hutch H9700T with slider**)
- Landing Gear: Two speed, crank on driver's side (Holland Atlas 55), channel bracing
- King Pin: Standard SAE, heat treated, **37" setting, 49" height, 3 I-beams with 5/16" plate**
- Cross Sills & Decking: **Keith 7/32"**, 3.0" cylinders, 24" wear strips (one end) **4" Jr I-Beams on 12" centers** with aluminum sub-deck,
- Clean Out: **Keith Hydraulic Clean Sweep system**
- Top: Flat design, open top, single center tie
- Top Cover: **Sioux City Electric roll over tarp system, 22oz vinyl material, w/remote, 6" arched front and rear caps**
- Tarp Bows: **Nine (9) 6" arched tarp bows spaced out evenly**



Rear Door: Full opening, **top hinged / side hinged combination door**, with solid aluminum skins with (2) latches

Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **Safety screens on front and under drive**

Ladders: **One located at front and one located at rear**

Rope Hooks: None

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted black**

Weight: Approximately 13,850# (+/- 3%)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.