

HALE TRAILER BRAKE & WHEEL

A034638-A034659
VIN: 080124-080145

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Trailer Model: FB8X45SS-OTR-70H

Axle: 30,000 lb.

Tire: [295/75R-22.5

Color: [Red



Special Instructions:

- Crane counterweight trailer
- Custom fabricated main beam construction (80 KSI web w/ 100 KSI beam flanges)
- 45' overall length
- 102" wide x 10' long upper wood deck w/ rub rail and stake pockets
- 33' lower open deck
- (2) 30,000 lb. AXN air brake axles
- Hutch 9700 spring suspension w/ 109" spread axle spacing
- Upgrade to 295/75R-22.5" dual tire and wheel assemblies
- Bendix ABS air kit
- 40" deck height
- 3 lb. grating welded on lower deck in areas not occupied by counterweights
- (2) bolt-on steps for accessing lower deck - (1) on each side
- (3) sets of pin housings to lock counterweights all on lower deck w/ high locking position only
- (12) 1" bent D-rings on lower deck - (2) sets for each counterweight location
- (2) Boom rests - (1) at rear of upper wood deck and (1) at rear of lower deck
- Single poly fenders on rear axles
- Dual Jost A420 semi-style landing gears w/ **low-profile sand shoes**
- Customer providing their own DOT tape and mud flaps
- Axles, 71.5" Track w/ 109" Spread Axle Spacing

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.