

HALE

TRAILER

BRAKE & WHEEL



A034681-A034690
VIN: 466601-466610

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

GVWR

GVWR:	Trailer to meet 40,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT HyCube

GEOMETRY

Length - Exterior:	28'-0"
** Length - Interior:	27'-2" Nominal
Width - Exterior:	102.36"
** Width - Interior:	101"
Height - Exterior:	13'-6"
Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	30"
Landing Gear Location:	74" from King Pin (+ 1"/-1/4", For Single Axle Tractor)
Pintle Hook & Height:	34" +/- 1" Ground to Centerline

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
* Wheel Finish for Steel:	Hot Dip Galvanized.
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

UPPER COUPLER

Approach Plate:	7/32" THICK 80,000 LB YIELD - 6 SUPPORT CHANNELS
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
Front Bottom Rail:	Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
* Upper Coupler Tube Q't'y:	(2) Tubing Application (Pintle Hook / Lift Gate /when harnesses & wires covered with Poly split / etc...) - Joggled

BODY/BASE

Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 8" C/L
Slider Body Rail (VT):	80" HT Fabricated "Z" Rail (For Single Axle Bolting Type)
Slider Rail Supplier:	HT Fabricated "Z" Rail (For Single Axle, Bolting Type)

FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
---------------------	--

* Floor Specification:	1.38" (1-3/8") Net Domestic Laminated Oak Hardwood - Havco Brand Only (10 years warranty)
* Floor Ratings - VT:	20,000 lbs Rated Floor per TTMA
Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

FRONT

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
* Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid (Bottom Open)
Front Receptacle(7-Way):	Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug
Options - Front Receptacle(7-Way):	Phillips QCS Plug connector
* Gladhand/7-Way Location:	(Exterior Harness Routing) Overlaid on Lower Roadside Front (STD) - Mounted on external overlaid HDG mounting bracket
* Corner Radius Protector:	(2) 0.125" X 12" SMOOTH Alum Each Side at Top

SIDE

Side Material:	0.05" Aluminum Prepainted White w/ natural color rivets
Side Posts:	0.45" Deep 14 Gauge Galv Steel "A" Slotted Logistic Posts
Side Post Centers:	16" C/L with 12" C/L @ Upper Coupler and Support Gear
Side Top Rail:	Shallow Post Side Top Rail
Side Bottom Rail:	Side Bottom Rail STD
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

REAR

Rear Frame:	Roll-Up Door, 6" Roll-Up Header (New Open Design)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
* Dry Van -WHITING RU:	Whiting Roll-Up Door. 1/2" Premium Plate
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal
Option - Horiz Member/Other:	One piece roll formed w/continuous welding
Underide Bolt Spec.:	Geomet bolts & nuts - Standard
* Dock Bumper:	Pair 3 X 5.88 HT High Performance Polyurethane Radius Bumper ATRO Black Color
Rubber Bumper Location:	Inboard of Light Protector Bars (Standard)
* Track Protector:	10Ga x 48" High Galvanized Steel Roll-Up Door Track Protector
* Door Accessories:	Roll Up Door Standard Door Components
Pintle Hook-Main Spec.:	Install Premier 2200 Pintle Hook without Quick Guide
P-Hook Mt'g Plate Finish:	Hot Dip Galvanized
P-Hook Shut Off Valve Spec.:	Standard Application
P-Hook Shut Off Valve Location:	Standard Application
P-Hook 7-way Receptacle:	HT Standard Socket
* Rear Frame Design:	Rear Frame Enclosed Door Sill Design

LIFT GATE

ROOF

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

LINING/SQUEE

Side Lining:	0.235" HDPE Recycled Plastic Installed between Posts
Front Lining:	0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height

* Base Side Scuff: 0.63" x 12" High White Recycled Plastic
 Side Scuff Band Mounting Method: Mounted Directly to Posts
 * Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)
 * Logistic Track: (2) Row of "E" Track, Galvanized - Overlaid, Both Side
 ** Logistic Track Location: Customer to advise
 * Logistic Track Installation: Standard Installation
 Front Corner Lining Support: Galv Steel Front Corner Liners

LANDING GEAR

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
 L/Gear Mt'g Method: Inboard Mounting (Standard)
 L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
 L/Gear Ground Clearance: Nom. 12" Ground Clearance
 L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
 L/Gear Crank Handle: Roadside
 L/Gear Options: None (HT STD)
 L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type: Fixed Single(1) Axle Bogie
 Axle Spacing: None (For Single Axle)
 Axle ABS System: Single Axle w/2S1M ABS System
 Bogie & Axle Location: Location to be Fixed at 40" From Rear (Single Axle)
 Option-Related Bogie Stopper Feature: None due to Single axle
 * Susp. Manufacturer: Hendrickson
 Suspension Capacity: Standard Duty
 * Hendrickson Susp. Specification: Hendrickson Intraxx AAT23K Air Ride - Single Axle
 Surelok (Anti-Dock): No Surelok (No Anti-Dock)
 * Susp. Dump Valve: Manual Dump Valve
 Locking Pin Mechanism: None (For Single Axle or Fixed Suspension Application)
 Susp. Sub-Frame: Supplied by Hyundai
 * Type of Susp Spring: Air Bag
 * Spring Specification: Air Bag
 * Axle Diameter: 5.75"
 * Axle Supplier: Hendrickson
 * Axle-General Spec.: Axle - Single (1) Axle included in Suspension (For 2S1M or 2S2M System)
 Axle-Track Length: 77-1/2"
 * Axle-Spindle Type: Parallel Spindle
 Brake Lining Size: 16.5" X 7" Drum Brakes
 * Brake Lining Spec.: Hendrickson Extended Service H20
 Brake Control System: 2S/1M Wabco iABS
 Spring Brake Control: Sealco 110500 Springbrake Priority
 * Brake Cont-Filter & etc.: Install Haldex Relay Valve (Booster Valve)
 Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)
 * Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
 * Brake Chamber Spec.: Wabco Premium Chamber
 * Stroke Length: 3" Long Stroke Length
 * Hub Specification: Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083939, Parallel Spindle
 Drum Specification: Conmet Cast Drum
 Hub/Drum-Opt(Nut&Other): Standard
 Bearing Specification: Stemco
 * Lubrication Spec.: Chev Delo (Syn) Grease
 * Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
 * Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include
 Hendrickson Hub Cap for TireMaax)
 Tire Inflation Pressure: 100 PSI

- * Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted at 24.6" from bottom of front panel over corner radius. (STD location)
- * Tire Inflation Lamp Spec.: 33 Series Lamp

ELECTRICAL

- * Harness-General Spec.: Molded Color Code Phillips Harness with QCS Plug
- Harness-Special Feature: Manufacturer's Standard Feature
- * Front Light: (2) Trucklite 33275Y LED PC Rated Mounted with Grommet
- * Rear ID Header Light: (5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
- * Rear ID-Special Feature: Dual Function Rear Header Lights: 3 center marker lamps with stop function, and 2 outboard marker lamps with turn function
- Rear Side Marker Type(Shape): Mini Button Style Lamp with Antitheft Bracket
- * Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
- Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD
- S/T/Tail Light-Quantity & Type: (4) Trucklite 40 or 44 Series (Round Style) or Equivalent
- * S/T/Tail Light-Detail Spec: (4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets
- Main Mid-Turn Light: Do Not Install the Mid turn lamp
- * ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
- ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD
- * License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange
- * Dome Lamp-Spec.: Trucklite #44339C LED Round Dome Lights
- * Dome Lamp-Quantity: Install (1) One
- * Dome Lamp-Location: Evenly Spaced From Rollup Door in Up Position at C/L of Ceiling
- * Dome Lamp Switch: Recessed Toggle Switch at Lower Rear Curbside & Pressure Switch-Tramec 38046X (HT STD)
- * Dome Lamp Circuit Connection: Blue Circuit: Auxiliary Continuous Power (STD Application)
- * Pressure Switch Location: Inside Upper Coupler
- Option Related Harness/Wiring: Standard
- Electrical Related Regulation: Standard Application

MARKING/DECALS

- HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
- Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
- Decal Opt 2-Decal Location: Standard Application
- Decal Opt 3-Decal Installation: Standard Application
- Conspicuity Vendor: 3M
- Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
- License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate
- License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill
- Furnish Document Holder: Factory Furnished
- Document Holder Detail Spec: (1) Phillips 16-802
- Document Holder/Manifest Loc.: Overlaid on Lower R/S Front
- Warning Decal Install Instruction: HT standard installation

PAIN/PAINT

- Upper Coupler Finish: Galvanized-Whole upper coupler section
- Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
- Axle & Components Finish: Black Undercoating
- * Susp. Sub-Frame Finish: Hot Dip Galvanized for Single Axle Sub-Frame (Frame Only)
- L/Gear(K-Bracing) Finish: Hot Dip Galvanized
- L/Gear(Upper Leg) Finish: Hot Dip Galvanized
- Rear Frame-Finish: Hot Dip Galvanized
- Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)
- * Rear Underride-Finish & Spec.: Hot dip galvanized & welded horizontal member w/pintle hook (for fixed single axle

application)
Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

MISCELLANEOUS

Mudflap Provider: Factory Furnished Mudflaps
Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Location: Single Axle in house frame (With Pintle Hook)
Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer
Mudflap Bracket design: 1 Piece Bracket
** Lift Pad Spec.: Install HT Occasional use lift pads for delivery, with HYUZ decals

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.