

HALE TRAILER

BRAKE & WHEEL



A034742-A034750
VIN: 577689-577697

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Infinity Flat 45' Air Slider Forklift Trailer (Model Code: HAIFL42SAT)

- Length / Width:** 45 feet x 102 inches
- Suspension Type:** Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
- Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
- Flooring:** 1 1/8 inch aluminum with 4 wood nailer strips
- Crossmembers:** 12 inch centers - 4 inch jr. I-steel
- Single Coil Hauling Package:** Included
- Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact
- Chain Cargo Tie Downs:** None standard
- Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
- Rubrail:** Integrated with siderail
- Main Beams:** 130K load bearing flanges
- Kingpin:** 30 inches
- Loaded Fifth Wheel Height:** 49 inches
- Landing Gear:** OEM Standard with Forward & Rear Bracing
- Knee Braces:** Fabricated on approx. 60 inch C/C
- Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front
- Bulkheads:** Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets (*BULKHEAD MUST BE INSTALLED & REMAIN ON TRAILER AT ALL TIMES AS PART OF FRONT COUNTERWEIGHT)
- Number of Axles:** 2
- Axle Spindle:** Tapered
- Brakes:** Spring brakes, auto slacks
- Air Line Filters:** (2) Meritor In-line type installed
- ABS:** Meritor Wabco iABS 4S/2M - no cable or tool
- Axle Spread:** 49 inches
- Hub and Drums:** 10-hole hub-piloted with outboard cast drums
- Wheel Ends:** Grease in hubs - *** 5-year wheel end warranty ***
- Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
- Tires:** 11R 22.5 14PR OEM standard tires
- Tire Inflation System:** None standard
- Suspension Detail:** Hendrickson AAZNT46K Intraax air ride slider -2 stop adjustable (Approx. 16 in. total slide range)
- Air Assist Slide Box Pins:** Standard mount of controls on slider frame
- Auto Glad Hand Dump :** Installed
- Front Corners:** Tapered steel
- Electrical System:** LED: 3 lights/side, 2 lights/side on rear - STANDARD
- Paint:** Black urethane on steel parts with Infinity decals - STANDARD
- Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails
- Bumper:** Weld-on hinged type; Uprights notched inside for additional fork clearance
- Mudflaps:** 1 set OEM standard behind rear axle
- Spare Tire Carrier:** None standard
- Winch Track:** Full length integrated double L type aluminum on both sides -- STANDARD
- Sliding Winches:** 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
- 27 foot Winch Straps:** None standard
- 30 foot Winch Straps:** None standard
- Dock Bumpers:** Not available due to design
- Hubodometer:** None standard
- Registration Holder:** Install registration holder - OEM standard
- Tool Box:** None standard
- VIN Plate:** Bilingual US/Canadian VIN plate
- Forklift Kit:** Factory installed Fontaine design with adjustable curved upper wheel stops which accepts most Princeton, Moffett, & Navigator brand lifts
- Forklift Kit Note:** *Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported.
**Actual brand & model to be advised to confirm compatibility
- Forklift Kit Lower Tire Supports for Moffett:** Removable lower "Moffett" tire supports each side
- Front Counterweights for Maximum 7,000# Forklift Weight:** Steel plates recessed in floor at front
- Please Note:** Price includes commodity surcharges
- Unit Numbers & Decals:** Not installed

Estimated Weight (lbs) (+/- 3%)

12,686

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.