

# HALE

## TRAILER

BRAKE & WHEEL



A034832-A034835  
 VIN: Q52332, Q52485,  
 Q52486 & Q52488

### SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

HYDRAULIC DETACHABLE GOOSENECK	Description	Model: RTN55TD3-R4A TRAILER
TONS CAPACITY	55 TONS IN ANY 12'	
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL	
OVERALL LENGTH	APPROXIMATELY 53'-0"	
PLATFORM WIDTH	8'-6"	
PLATFORM LENGTH	26' (OVERALL LENGTH MUST BE 53'-0" OR LESS AND MUST HAVE 43'-0" OR LESS FROM THE 90" SWING TO THE CENTER OF MIDDLE AXLE).	
PLATFORM HEIGHT/ROAD CLEARANCE	18"/6" LOADED-ADJUSTABLE (12" DEEP MAIN BEAMS)	
CROSSMEMBER SPACING	ON 20" CENTERS	
FRONT FOLDING RAMPS	STEEL WITH TRACTION BARS	
FRAME REINFORCEMENT	FOR A 3+1 (14'-1" SPREAD)	
TOP FLANGE REINFORCEMENT	OUTSIDE OF OUTER BEAMS ONLY	
BUCKET TROUGH	LAST 3 CROSSMEMBERS OF DECK	
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE	
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT	
GOOSENECK SUPPORT CYLINDER	HYDRAULIC	
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN	
SWING CLEARANCE	108" & 90"	
FIFTH WHEEL HEIGHT (50" LOADED)	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)	
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA	
ALUMINUM HINGED AND LOCKABLE COVER	AT REAR OF GOOSENECK	
CHAIN AND BINDER RACK	W/ BASE PLATE AT REAR OF GOOSENECK	
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS	
ALUMINUM AIR TANK		
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)	
SPRING BRAKES	ON 2ND AXLE	
AXLES	(3) 25,000# 3/4" WALL W/ 23,000# BRAKES AND LIMIT CHAINS	
TIRES	(12) 275/70R22.5 (H)	
ACCURIDE ALUMINUM WHEELS	ACCUSHIELD OUTERS, STANDARD POLISHED INNERS	
SUSPENSION	AIR RIDE W/ 52" AXLE SPACING	
SUSPENSION	AIR LIFT 3RD AXLE ONLY	
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL	
RAISING AND LOWERING VALVE	AT REAR OF TRAILER	
LIGHTS	L.E.D. RUBBER SEALED SYSTEM	
AMBER L.E.D. STROBES	IN 3RD TAIL LIGHT POSITION W/ SWITCH	
BATTERY BACK-UP	W/ RECHARGEABLE FEATURE	
LASH RINGS	(24) TOTAL, 9-PER SIDE, BENT STYLE, 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END FLAT STYLE	
ADDITIONAL FLAT STYLE LASH RINGS	(2) PER SIDE IN BUCKET TROUGH EVENLY SPACED	



EXTENSION BRACKETS (OUTRIGGERS)	12" SWING/REMOVABLE WITH DOUBLE HOOK-ON FRONT. "FULL LENGTH" OF DECK
DECKING	1-1/2" APITONG (OUTSIDE MAIN BEAMS ONLY)
PAINT	PAINT ONLY THE GOOSENECK WEBS, DECK WEBS, EXTENSION BRACKETS, REAR SECTION WEBS, END OF BOLSTERS, REAR LIGHT PANEL WEBS. ETNYRE RED (2-PART URETHANE)
HOT DIP GALVANIZE	ENTIRE TRAILER
BOOMWELL	OPEN BOTTOM W/ EXTRA LOW 1ST CROSSMEMBER (BOLT-IN COVER PLATE)
TRACTION BARS	ON FRONT & REAR SLOPES
CHAIN HOOKS & FLAG HOLDER SLOTS	ON BOLSTERS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
AIR AND ELECTRICAL CONNECTIONS	FOR FUTURE FLIP/REMOVABLE AXLE
ALUMINUM STORAGE BASKETS BOLT-IN	(1) FRONT OF DECK, (1) AT REAR OF DECK
FLIP/REMOVABLE AXLE	(1) 25,000# 3/4" WALL AXLE, (4) 275/70R22.5 (H) TIRES, ACCURIDE ALUMINUM WHEELS (ACCUSHIELD OUTERS, STANDARD POLISHED INNERS), RAISING AND LOWERING VALVE, AMBER L.E.D. STROBES IN 3RD TAILLIGHT POSITION, BATTERY BACK-UP W/ RECHARGEABLE FEATURE, FLAG HOLDERS W/ THUMB SCREWS. HOT DIP GALVANIZED

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.