

# HALE TRAILER BRAKE & WHEEL



A034882-A034884  
VIN: 49801-49803

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

Base Model #: DF53-BTR x 102 Air Spread

Serial #: 49801 - 49803

## components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 13,990# - Including Length of Beavertail

UPPER DECK LENGTH 10' Length = 59" Height

LOWER DECK LENGTH 38' Length = Front 41", Center 42" Rear 40" Heights

DOVETAIL 60"- 15\* Steel Smooth Plate & Traction Bars

OVERALL WIDTH 8' 6"

KING PIN SETTING 18" - Squared Front

UPPER COUPLER PLATE 3/8" (+)53#

UPPER COUPLER HEIGHT 48"

MAINFRAME 26" PreCamb Beam-130K Tru-Strength Flanges - Limited Lifetime Warranty

BULKHEAD None

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE NONE

FLOOR DECKING 1-1/8" Apitong

WINCH TRACK Steel Slide Entire Length of Road Side Only

WINCHES 18 Zinc Coated (5 Upper Deck)

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles - 22.5

SUSPENSION LOCATION King Pin to Center of Rear Axle 43'

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

DUMP VALVE Electric Rear Axle and Manual Dump All Axles

LIFT AXLE None

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHIELDS None

WHEELS Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)

TIRES 255/70R 22.5 - Firestone FS560

TIRE INFLATION SYSTEM None

STAKE POCKETS 24" O.C. & 4 Across Front

ANTI-SAIL MUD FLAPS Behind All Axles

PIPE SPOOLS Double

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

\*\*Continuous Rub Band From Lower Deck To Tail Section.\*\*

DOCK BUMPERS None

LOADING RAMPS (2)-Spring Assisted

\*\*Fully Galvanized Ramps, Springs and Crossbars.\*\*

CONTAINER TWIST LOCKS None

CARGO TIE DOWN None

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

TOOLBOX MATERIAL Aluminum- Smooth Box & Doors

TOOLBOX TYPE 18Hx18Dx60L-Alum Box-Barn Style Double Door- CAM LOCK STYLE 17-PRT-AH596

TOOLBOX LOCATION Driver Side- Between Spread

LIGHTS Accent Total LED Pkg- 7 Micros Per Side & Mid Turn-3/3/3 Rear

CUSTOM LIGHTS Strobe Kit- 3-3-3 Toggle Switch - D/S - Rear Trailer

PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DECAL PACKAGE Standard Dorsey Logo Kit

CUSTOM 1. Grote Document Holder Landing Gear R/S

CUSTOM 3. Inline Air Filters

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.