

HALE

TRAILER

BRAKE & WHEEL



A035150-A035161



VIN: 473601-473612

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

GVWR

* GVWR:	Trailer to meet 80,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
* Product Type:	HT Steel Duralite

GEOMETRY

* Length - Exterior:	40'-0"
Width - Exterior:	102.36"
* Fifth Wheel Height:	49"
* King Pin Location:	30"
* Landing Gear Location:	108" from King Pin (+ 1"/-1/4")
Duralite Front Deck Height:	59-3/4" (± 1/2")
Duralite Rear Deck Height:	54-5/16" (± 1/2")

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Double Coin FT105
* Tire Size:	11R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole/10 Stud Holes (Steel, Inner & Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	Myers TR-572-F19 Valve stem

UPPER COUPLER

* Approach Plate:	3/8" thick 50,000 Lb Yield (Duralite)
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin

DURALITE OPTIONS

* Cross Members:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Main Web:	3/16" Thick. Welded One Piece Type (110 KSI Domex)
Top Flange:	3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type
* Bottom Flange:	1/2" Thick, 100 KSI Domex, 5" Wide One Piece Type
Holes on Main web:	Diamond Shape
Gusset Type:	Pipe Type
Gusset Specification:	(3) on Each Side (HT STD)
* Front Sill:	HT Standard 3/16" Steel
* Front Stake Pockets:	4 EA for Steel Bulkhead Installation
* Bulkhead:	Steel Removable Type - Hot Dip Galvanized
* Bulkhead Specification:	48" High x No Wrap
* Bulkhead - Options:	Welding steel panel type on bulkhead.
* Rear Sill:	HT 9" Steel 3/16# rear sill
* Side Rail:	HT Standard Steel Channel
Side Stake Pockets:	24" Centers on Each Side (STD)
Side Pipe Spools:	Double Spools between Stake Pockets (STD)
* Side Rub Rail:	3/8" Thick, 3" Rails on Both Sides

* Winch Rail: Aluminum Winch Rail for Sliding Winches OR Combination (SLD+ FIX) Winches
Winches: Sliding Steel Winches, (12) on Each Side
Sliding Winch Stoppers: Stoppers at Front and Rear (Flatbed STD for Sliding Winches)
* Main - Options: Rear step Ladder with handle integrated.
Fastener Options: Standard Fasteners

FLOOR

* Duralite Floor Specification: 1-5/16" Apitong Wood Floor (Steel STD)
Floor Screws: HT Duralite Standard (2 Screws Per Board on I-beams)

FRONT

Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid Straight Type
Front Receptacle(7-Way): HT Duralite Standard (Phillips 7-Way Integrated with Main Harness)
Gladhand/7-Way Location: (Interior Harness Routing) Overlaid on Lower Centerline Front

REAR

Rear Underride Guard: 4" Tube Bolt on Assembly w/ Bolt on Perforated(Pooched) Horizontal
Dock Bumper: Pair Heavy Duty Dock Bumper (Ref. Buyers B4500)
Rubber Bumper Location: HT Duralite Standard Location

LANDING GEAR

** L/Gear Spec.: SAF Holland Mark-V LGS-3C305-AX0485
* L/Gear Shoes: 18" X 18" X 4.5" Sand Shoe - For Holland Mark-V
L/Gear Crank Handle: Roadside
* L/Gear Cross Brace Design: HT standard cross Brace attachment design & additional forward reinforcement.

RUNNING GEAR

Bogie Type: Sliding Tandem(2) Axle Bogie
Axle Spacing: 49" Axle Spacing
Axle ABS System: Tandem Axle w/2S1M ABS System
Duralite Bogie & Axle Location: HT Sliding Axle STD Location (CA Compliant; KP to Rear Most Axle 40#)
* Susp. Manufacturer: Hutchens
Suspension Capacity: Standard Duty
* Duralite Susp. Specification: Hutchens H9001 4-Pin Platform Slider
Surelok (Anti-Dock): No Surelok (No Anti-Dock)
* Locking Pin Mechanism: Manual Pin Puller (Flexi Pull) or (EZ Pull)
* Type of Susp Spring: Mechanical Leaf Spring
* Spring Specification: 3 Leaf - Medium Arch (H355-00)
* Axle Supplier: Meritor
* Axle-General Spec.: Axle - Tandem (2) Axle no included in Suspension w/ 2S1M or 2S2M System
Axle-Track Length: 77-1/2"
Axle-Spindle Type: Parallel Spindle
Brake Lining Size: 16.5" X 7" Drum Brakes
* Brake Lining Spec.: Meritor MA212 Q+ (Meritor STD)
* Brake Control System: 2S/1M Wabco iABS
Spring Brake Control: Sealco 110500 Springbrake Priority
Drain Valve & Other: Parker DC604-4 Drain Cock
* Slack Adjuster Spec.: TSE Slack Adjuster Part # TSE07135S. Auto-5.5#, 28 Spline
Brake Chamber Spec.: TSE 3030 Tamper Resist (HT standard)
Stroke Length: MFG's Standard Stroke Length
* Hub Specification: Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083939, Parallel Spindle
* Drum Specification: Conmet Cast Drum
Hub/Drum-Opt(Nut&Other): Standard
Bearing Specification: Stemco
Lubrication Spec.: Chev Delo Gear EP5 80-90 oil
Wheel Seals Spec.: Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut

ELECTRICAL

* Harness-General Spec.: Molded Color Code Phillips Harness (Sta-Dry) with Locking Device connector

Harness-Special Feature:	Manufacturer's Standard Feature
* ID/Marker Light Spec:	(3) Phillips 3/4" Penny ID / Marker Light & Anti-theft (with locking device connector)
* S/T/Tail Light-Detail Spec:	(6) Phillips 51-HY40202 4" Round STT w/Flange-Red (3 on each side)
* Main Mid-Turn Light-Detail Spec:	(2) Phillips 51-HY60303-0 LED 6.5" Oval MidTurn/Marker - Amber Surface Mount with Stainless Steel Cover Ring 51-60904
* ABS Light Detail Spec:	(1) Phillips 51-HY37323 Amber 3/4" Penny, PC Rated w/anti-theft hardware
* License Light:	(1) Phillips 51-HY37721-0 (Button Style, Clear) with Grommet (19mm Hole Required)
* Option Related Lamps/Harness:	Additional Phillips Amber Marker Penny Lights. (2) Each Side, Evenly Spaced Front to Rear (total 4 extra lights). Front, midturn, rear marker & (2) additional markers evenly spaced

MARKING/DECALS

Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	HT DuraLite Standard Location
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front

PAINT/FINISH

Axle & Components Finish:	Black Undercoating
Susp. Sub-Frame Finish:	Black Undercoating
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
* L/Gear(Upper Leg) Finish:	Hot Dip Galvanized
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Bolted Horizontal Member
Duralite Product Finish:	Hot Dip Galvanized

MISCELLANEOUS

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x24" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Method/Install:	STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.