

HALE TRAILER BRAKE & WHEEL



A035171-A035212
VIN: 093286-093327



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ALUMINUM "BST" PLATFORM TRAILER

LENGTH:	48'	SUSPENSION:	AAT25K / E2-1 (3)(6)(7) GALVANIZED HANGERS
WIDTH:	102"	LOWERING KIT:	AUTOMATIC
NOSE:	SQUARE - 7 WAY + AUX ISO 7 WAY AIR AND ELECTRIC IN CENTER POSITION	AXLE TO AXLE:	98"
KING PIN SETTING:	30" SETTING w/ 1/4" PLATE	AXLE TO REAR:	30"
FLOOR:	HD KNURLED ALUM W/ 2 NAILERS INTEGRATED - DBL "L" SIDE RAIL CENTER TIE DOWN TRACK	LIFT / AXLE:	NONE
XMEMBER SPACING:	22" SPACING	SPACING:	
COIL PACKAGE:	YES - CENTER	F.W. HEIGHT:	49"
SPOOLS:	DOUBLE	CONTROLS:	
POCKETS:	HD	AXLES:	TP - HXL-5
ROPE HOOKS:		AUTO SLACKS:	HALDEX (TSE Omnibrake LTRT Long Stroke Chmbr)
TIE DOWNS:	12 PAIR	BRAKES:	16-1/2" X 7"
MARKER LIGHTS:	LED - 2 PR + MMTS (2)	ABS SYSTEM:	2S/1M STANDARD BRAKE VALVE
MID TURN SIGNAL:	COMBO MRKR / MMTS BELOW RAIL (2)	HUBS:	10 STUD STEEL; HXL-5; GREASED CAST DRUMS (4)
FLAT  ANGLE 		WHEELS:	8.25 X 22.5 8 ACCURIDE SP TR-554 VALVE STEM / V2B VALVE CAPS
LIGHT PANEL:	LED - 9 LIGHTS OOS ooo SOO - LED (2)(8) FULL WIDTH BUMPER	TIRES:	295 / 75R X 22.5 BS R196A 14-PLY TIRE MAXX PRO BOTH AXLES
BULKHEAD:	NONE	LANDING GEAR:	JUST AX-150 D/S CRANK (5) SHORTER BRACING
TYPE:		TIRE CARRIER:	NONE
HEIGHT:		TOOLBOX:	QTY: TWO - AERO
RETURNS:		SIZE:	24' X 24" X 48"
MAT'L:		LOCATION:	BETWEEN AXLE EACH SIDE
ACCENT TAPE:	BLACK (1)	MAT'L:	SMOOTH; DBL DOOR; CAMLOCK STYLE, 1/8"
PAINT:	BLACK	MUDFLAPS:	STD
WINCH TRACK:	INTEGRATED DOUBLE "L"	TYPE:	SILVER PLASTIC
LOCATION:	BOTH SIDES	LOCATION:	AT REAR
WINCHES:	26 - ZINC COATED SLIDING (16 D/S-10 P/S)		
WINCH CLIPS:	NONE		
STRAPS:	NONE		

WEIGHT :+/-3%: 9903

REMARKS:

1. CONSPICUITY TAPE ON MAIN BEAM NOT ON TARP BAR
2. ALL LIGHTS TO BE RUBBER GROMMET & BOXED IN BELOW RAIL.
3. NECK CUT MOVED 18" AHEAD OF STANDARD
4. STEMCO #650-0610 HUBOMETER D/S FRONT AXLE.
5. MOUNT LANDING GEAR 126" FROM THE FRONT OF TRAILER TO C/L OF LANDING GEAR. ADD GEAR TRUCKLITE #97960 MOUNTED D/S @ LANDING GEAR
6. REAR DECK HEIGHT SET AT 56" FOR ADDITIONAL GROUND CLEARANCE.
7. MERITOR 10 MPH AUTO-REINFLATE ON REAR AXLE & WIRED TO AUXILIARY ISO 7 WAY & TOGGLE SWITCH ON D/S FRAME
8. TOGGLE SWITCH @ REAR OF TRAILER FOR THE STROBES. S = STROBES
9. 8 PR OF OLD STYLE CHAIN TIE DOWNS - LOCATIONS TBD
10. WIRE DROP AT D/S FRONT CORNER FOR AERO & WIRE DROP AT P/S FRONT FOR GPS SYSTEM.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.