HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

| | | | |
|---|---|---|---|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A035239-A035246

VIN: 577701-577708

## Infinity Flat 45' Air Slider Forklift Trailer (Model Code: HAIFL42SAT)

| |
|---|
| **Length / Width:** 45 feet x 102 inches |
| **Suspension Type:** Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements |
| **Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads |
| **Flooring:** 1 1/8 inch aluminum with 4 wood nailer strips |
| **Crossmembers:** 12 inch centers - 4 inch jr. I-steel |
| **Single Coil Hauling Package:** Included |
| **Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact |
| **Chain Cargo Tie Downs:** None standard |
| **Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets) |
| **Rubrail:** Integrated with siderail |
| **Main Beams:** 130K load bearing flanges |
| **Kingpin:** 30 inches |
| **Loaded Fifth Wheel Height:** 49 inches |
| **Landing Gear:** OEM Standard with Forward & Rear Bracing |
| **Knee Braces:** Fabricated on approx. 60 inch C/C |
| **Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front |
| **Bulkheads:** Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets (*BULKHEAD MUST BE INSTALLED & REMAIN ON TRAILER AT ALL TIMES AS PART OF FRONT COUNTERWEIGHT) |
| **Number of Axles:** 2 |
| **Axle Spindle:** Tapered |
| **Brakes:** Spring brakes, auto slacks |
| **Air Line Filters:** (2) Meritor In-line type installed |
| **ABS:** Meritor Wabco iABS 4S/2M - no cable or tool |
| **Axle Spread:** 49 inches |
| **Hub and Drums:** 10-hole hub-piloted with outboard cast drums |
| **Wheel Ends:** Grease in hubs - *** 5-year wheel end warranty *** |
| **Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD |
| **Tires:** 11R 22.5 14PR OEM standard tires |
| **Tire Inflation System:** None standard |
| **Suspension Detail:** Hendrickson AAZNT46K Intraax air ride slider -2 stop adjustable (Approx. 16 in. total slide range) |
| **Air Assist Slide Box Pins:** Standard mount of controls on slider frame |
| **Auto Glad Hand Dump :** Installed |
| **Front Corners:** Tapered steel |
| **Electrical System:** LED: 3 lights/side, 2 lights/side on rear - STANDARD |
| **Paint:** Black urethane on steel parts with Infinity decals - STANDARD |
| **Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails |
| **Bumper:** Weld-on hinged type; Uprights notched inside for additional fork clearance |
| **Mudflaps:** 1 set OEM standard behind rear axle |
| **Spare Tire Carrier:** None standard |
| **Winch Track:** Full length integrated double L type aluminum on both sides -- STANDARD |
| **Sliding Winches:** 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD |
| **27 foot Winch Straps:** None standard |
| **30 foot Winch Straps:** None standard |
| **Dock Bumpers:** Not available due to design |
| **Hubodometer:** None standard |
| **Registration Holder:** Install registration holder - OEM standard |
| **Tool Box:** None standard |
| **VIN Plate:** Bilingual US/Canadian VIN plate |
| **Forklift Kit:** Factory installed Fontaine design with adjustable curved upper wheel stops which accepts most Princeton, Moffett, & Navigator brand lifts |
| **Forklift Kit Note:** *Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported. **Actual brand & model to be advised to confirm compatibility |
| **Forklift Kit Lower Tire Supports for Moffett:** Removable lower "Moffett" tire supports each side |
| **Front Counterweights for Maximum 7,000# Forklift Weight:** Steel plates recessed in floor at front |
| **Unit Numbers & Decals:** Not installed |
| |
| |

| | |
|---|---|
| **Estimated Weight (lbs) (+/- 3%)** | **12,686** |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.