

HALE

TRAILER

BRAKE & WHEEL



A035438-A035439
VIN: 941007 & 941010

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Description

EA NEW ACE ROLL OFF TRAILER - ART-60-402

Overall Length: 40' 11"
 Container Frame Length: 40'
 Kingpin to Last Axle: 34'
 Rated 60,000 lbs. Lift Capacity
 Container Size Range- 10'-40' Outside Rail Containers

MAIN FRAME:

12"X 4"X 1/4" Rectangular Tubing
 12"X 4" Cross Members for Main Frame
 Top Wrap: 1/2" X 4" Flat Bar Wear Pad
 Bottom Wrap: 3/4" x 4" Flat Bar
 1/4" Hollow Truss Mounted Below Main Frame with
 1/2" X4" Bottom Wrap
 (2) 1 1/4" Fixed Stops at Front of Trailer
 (14) 3 1/2" Rollers Welded to Outside Frame
 3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar
 Stiffener

STABILIZER FRAME:

4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap
 Hinges: 2" Round Bar
 28"x16"x5/8" Draft Arm Support Plates

HYDRAULICS:

(2) 8.5" - 4 Stage Telescopic Main Lift Cylinder 133,000
 lbs. @ 2,400 PSI
 (2) Ace Independent Reeves: 3 1/2" Rod 7" Bore Reeving
 Cylinder 88,000 lbs. ea.
 Directional Valve with Pressure Gauges and Adjustable
 PSI - Set to 2,450 PSI
 Hoses: 3/4" 3000 PSI Hoses with Nylon Covering
 Hydraulic Pipes: 3/4" Steel Pipe
 Standard JIC Fitting on All Hydraulics
 NO HYDRAULICS IN REAR OF TRAILER

CABLE AND AFFILIATED COMPONENTS:

Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button
 with Cast Ring
 Pulleys: 10" Sheave with 2.5" Pin (Qty 3)
 Pulley Block - Independent (2)
 Independent Pulley Track

RUNNING GEAR:

Description	
	H900 50,000 lbs. Spring Single Point Suspension (Tandem) Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs & Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs.
	LIGHTING & SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights & Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added*
	PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace Axles & Suspension are subject to manufacturer discretion Main Frame Assy, Standard Tandem Finishing Stages, 40FT Tandem
PART	EA Electric over hydraulic wireless remote ready valve
80-3004	EA Removable Stop Set Driver & Passenger 3/4 Thk Stop For proper weight distribution on containers shorter than trailers overall length INCLUDED IN PRICE
252-3001-40H	EA Tarp System, Roll-Off Complete 40' Hyd Roll Rite (Hydraulic Tarp Motor) - Hydraulic Ace Tower
115-1003-I	EA Front Work Lights Installed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.