

HALE

TRAILER

BRAKE & WHEEL



A035451-A035456
VIN: S034198-S034203

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Infinity Flat 48' Closed Tandem Air Forklift Trailer (Model Code: HAIFL12CTA)

Length / Width: 48 feet x 102 inches
Suspension Type: Fixed closed tandem air
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: None standard
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkhead - Counterweight: Removable steel 4 post DOT type - no turnback - 48 inches high (*Bulkhead serves as added front counterweight which in many cases is needed to safely pull unloaded trailer w/rear-mounted forklift)
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Axle Spread: 49 inches - set ahead for fork clearance
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
Tires: 11R 22.5 14PR OEM standard tires
Tire Inflation System: None standard
Suspension Detail: Hendrickson AANT23K Intraax air ride
Auto Glad Hand Dump : Installed
Front Corners: Tapered steel
Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Weld-on hinged type; Uprights notched inside for additional fork clearance
Mudflaps: 1 set OEM standard behind rear axle
Spare Tire Carrier: None standard
Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD
Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: Not available due to design
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: None standard
VIN Plate: Bilingual US/Canadian VIN plate
Forklift Kit: Factory installed Fontaine design with adjustable curved upper wheel stops which accepts many Princeton & Moffett brand lifts
Forklift Kit Note: *Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported. **Actual brand, model, & weight should be identified to confirm compatibility
Forklift Kit Lower Tire Supports for Moffett: Removable lower "Moffett" tire supports each side
Front Counterweights for MAXIMUM 7,000# FORKLIFT : Steel plates recessed in floor at front In Addition To Steel Bulkhead Required & Noted Above
Counter Balance Note: FONTAINE WILL ONLY BE RESPONSIBLE FOR ISSUES RELATED TO CARRYING FORKLIFT MODELS WITH MAXIMUM WEIGHTS & CG'S AS SPECIFIED ABOVE
Unit Numbers & Decals: Not installed
Stacking: Price includes Standard stacking of each trailer
Structrual modifications: Install Counterweights at Front and Underneath Deck: *Recommended For Use With Heavier Forklift
Dealer Specified Options
Aluminum Air Tank
zinc winches
Estimated Weight (lbs) (+/- 3%)
13,591

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.