

# HALE TRAILER BRAKE & WHEEL



A035741-A035742  
VIN: P4087-P4088

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

Jeep Axle (Model: JEP FA 6090 60)	
AXJ609060RS	
	Est. Wt.: 2,430# +/- 3%
TRAILER - GENERAL	
<b>Compatibility:</b> Magnitude 60HD, 65, 75 and 80 ton	
<b>Compatibility:</b> Magnitude 453 Jeep Axle	
<b>Length:</b> 5 feet 0 inches	
<b>Width:</b> 8 feet 6 inches	
AXLES	
<b>Number of Axles:</b> 1 axle	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle <b>NOTE: GAWR determined by suspension type, brakes, tires and other components.</b>	
<b>Axle Spread:</b> 60 inches (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Dust Shields on Flip Axle:</b> None	
SUSPENSION	
<b>Suspension:</b> Air ride	
WHEELS AND TIRES	
<b>Wheels:</b> 8.25 x 22.5 Outer LVL One buffed/steel disc inside - hub-piloted	
<b>Tires:</b> 275/70R 22.5 OEM Standard	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
LIGHTING	
<b>Electrical System:</b> DOT sealed beam and harness	
PAINT	
<b>Paint:</b> Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
<b>Lash Rings:</b> 1 pair - 2 total	
<b>Flag Holders:</b> Flag holders - 1 pair located on rear bumper	
<b>VIN Plate:</b> Bilingual VIN plate	

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.