





A035788-A035790

VIN: 45393-45395

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Concord, NC: 800-438-2250 Delmar, DE: 866-486-1400 Des Moines, IA: 888-673-5011 Elkton, MD: 800-544-7127 Jacksonville, FL: 800-828-3055	Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Raleigh, NC: 833-418-9777 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 Walpole, MA: 800-854-5310
---	--

haletrailer.com | @haletrailer







800-232-6535 *FINANCING AVAILABLE

Model: AC3-30-AR (air)
Capacity in tons: 30

Pintle eye	Adjustable pintle eye (3" I.D.) with 48" chain and grab hooks
Tongue	5'-6" with lockable tool box with aluminum diamond plate lid
	Move hinge 4" forward
Landing Gear	2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard
Electrical receptacle	Seven pin connector
Headboard	8" high full width
Deck section design	One piece tongue, main beam and beavertail (cold formed)
Deck section length	30'-0" (24'-0" flat with 6'-0" beavertail)
Deck section width	8'-6"
Loaded deck height	33-3/4"
Flooring	1-1/2" apitong
	Individual wheel covers with wood between and behind them
Lash rings	20 total -
	8 each side on flat deck (straight style), 16 total
	1 each side on beavertail (straight style), 2 total
	1 each side on top of main beams, just behind headboard (swings front to back) (straight style), 2 total
Main beams	12" deep hi-tensile
Cross members	6" deep channel x 8.2# hi-tensile
Side members	8" deep hi-tensile
Beavertail	6'-0" Double break with wood flooring full width
Ramps	38" wide x 6'-6" length air ramps with wood flooring, stored vertically with lock bar
Number of axles	3
Axle capacity	25,000#, full width track
	GAWR = 21,420#

Brakes	12-1/4" x 7-1/2" air with 2S/1M ABS, type 30 chambers/6" auto slacks. Spring brakes on two axles.
Wheels	Aluminum/steel disc with oil seals (6.75 x 17.5), inner wheels steel, outer aluminum wheels polished
Tires	Twelve (12) 235/75R17.5 (H) 16PR radials Use valve stem extensions on inside wheels
Suspension	Air ride with air lift on axle 1 Air lift switch located on tongue 50,000# Hutch spring on axles 2 & 3, spring 365-00
Lights and wiring	12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK strobe lights mounted in rear ramps with switch in tool box (Ref. SN44570)
Paint	Valspar standard Talbert black
Estimated empty weight	12,660#
Additional general specifications	Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.