

HALE

TRAILER


BRAKE & WHEEL

A035943-A035954
VIN: S034684-S034695



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	*** Trailer rated 100 LBS fully open, self-supporting load. Trailer needs to be properly loaded per engineering. ***
LENGTH	53'-0" closed.
LENGTH OPENINGS	71'-0" opened. *** 78" overlap ***
WIDTH	5'-0" increments in closed position.
HEIGHT	102", 97" between side rails.
DROP HEIGHT	Floor, approximately 62" high at front and 40" at the bumper. 20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	1/2", plug welded structure.
KING PIN LOCATION	*** needs to be rated 44,000 LBS to get to 119,000 LBS GVWR.
COUPLER HEIGHT	18" from front. 50".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 1/2" x 6", 100 000 psi steel, 24" high. *** minimum of 78" overlap ***
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 13 1/2" above suspension.
WEB	1/4" plate full length, 80 000 psi steel.
GOOSENECK	12 1/4" high, with 54" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel. 16" center to center in gooseneck and the remaining 12" c/c.
FLOOR	Aptiong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	6" channel @ 8.2 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
ENDS	
FRONT RAIL	Formed steel 1/4".
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
BUMPER	Bracing for a *** flip up axle *** and (1) rubber dock at top front. same as U#236100.



ITEM	DESCRIPTION
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL REAR ADD. CONNECTOR STROBE LIGHTS TAIL LIGHTS	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams Grote, tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. 4 way. Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: REAR Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGH-4F010), heavy duty, with mounting plate, full galvanized 18" x 18". Galvanized. Road side.
BOGIE BASIC SUSPENSION BOGIE SUSPENSION LIFT DEVICE U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	Fixed. Hendrickson HT-250US (6.5), tandem, 60" spread. Hendrickson HT-250US (6.5) with Manac center lift. Located at 60" rear of tandem. Controled manually. *** Only 1 1/2" of clearance from the ground if used at rear. *** *** NO WARRANTY ON THE TIRES NOR GROUND AXLES, (FLAT SPOT) *** With nuts at bottom. Air. Hendrickson, HP-S506, 27 000 lbs. capacity. Welded. 28 splines. 77 1/2". None (Hendrickson axles). 16 1/2" standard, long life H26-HXS Hendrickson lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"), long stroke. (4 years warranty by T.S.E. for parts only). WEBB, 10 studs disc hubs, balanced drums 117 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. (Heavy duty 25000 lbs cap.) (Bearings HP). Alcoa, aluminum, half "ULTRA ONE vHub" and half steel. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts. Continental, 275/70 R 22.5 HSR2 SA 18 ply (38.0") ** GAWR 25000 LBS needed for 119,001 GVWR ***



ITEM	DESCRIPTION
AIR SYSTEM GLAD HANDS AIR VALVES VALVE(S) VALVE CONTROL BOX	aluminum air tank. Fixed, filter on the third glad hand at front. Meritor Wabco, IABS, 2 sensors 1 modulator. Fast-brake kit. Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Stainless steel air system for pin on axle.
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS EXTRA MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray. Qty: 2, rubber. Located: 1 at front of landing gear in between main frames, to protect the hoses coil, and 1 at front of suspension in between main frames, to protect air boosters.
FINISHING PAINT PAINT AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of epoxy primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. **Zinc** primer instead of epoxy primer. Color: black, code: PPG AU37-FP908. Color: black, code: PPG AU37-FP908. White. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS	same as U#236100 Estimated weight is 19,683 LBS +/- 3%
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.