

HALE

TRAILER

BRAKE & WHEEL

A035964-A035972

VIN: S034705-S034713



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	90'-0" open
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	24" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 1/2" x 6", 100 000 psi steel, 17 5/8" high. (For tandem suspension Only)
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	Formed channel 6" @ 4.6 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
X BRACES	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
SPACERS FOR RUB RAILS	Double between side boxes.
ENDS	
FRONT RAIL	9 gauge formed steel.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
BUMPER	Aluminum plate, bolted between bumper uprights to close rear.
POCKETS	2 welded pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.



ITEM	DESCRIPTION
CONTROL BOX	including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Stainless steel
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT PAINT BOGIE AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of epoxy primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. **Zinc** primer instead of epoxy primer. Color: black, code: PPG AU37-FP908. Color: black, code: PPG AU37-FP908. Same color as trailer. White. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS	same as U#236355 estimated weight is 17,123 LBS +/- 3%
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.