

HALE TRAILER BRAKE & WHEEL

A035973-A035975
VIN: S034714-S034716



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	FLIP AXLE FOR PLATFORM
DIMENSIONS	
LENGTH	61 1/2"
WIDTH	102"
COUPLING	
COUPLER PLATE	For anchor joints, 4 x 2" dia. rods and bushings.
STRUCTURE	
FLANGES	1/2" x 6", 100 000 psi steel.
WEB	3/16" plate, 80 000 psi steel. 13 1/2" high.
ENDS	
BUMPER	Rectangular steel tubing. Including supports with flag and excessif width sign.
ELECTRICAL	
FRONT CONNECTOR	Cord with 7 ways connector.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra blue LED, sealed beams, in a closed back rubber grommet. (tail lights with male pins #54332, markers #47122 (2 1/2" dia.), licence light #60280-M).
STROBE LIGHTS	Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: REAR
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (9), single.
U-BOLTS	With nuts at top.
SPRINGS	Air.
AXLE(S)	Hendrickson, HP-S506, 27 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (Hendrickson axles).
BRAKES	16 1/2" standard, long life H26-HXS Hendrickson lining.
BEARINGS	HM 518445.
SLACK ADJUSTERS	TSE S-ASA, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"), long stroke. (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 10 studs disc hubs, balanced drums 117 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. (Heavy duty 25000 lbs cap.) (Bearings HP).
RIMS	Alcoa, aluminum, half "ULTRA ONE vHub" and half steel. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts.
TIRES	Continental, 275/70 R 22.5 HSR2 SA 18 ply (38.0")



ITEM	DESCRIPTION
AIR SYSTEM GLAD HANDS AIR VALVES	Fix. Sealco, synflex 3/8" diameter.
ACCESSORIES REGISTRATION HOLDER MUD FLAPS	One plastic, Betts-PS-1 or equivalent. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT PAINT AXLE(S) PAINTED HUBS RETROREFLECTIVE TAPES	Shot blasted, one coat of zinc primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. **Zinc** primer instead of epoxy primer. Color: black, code: PPG AU37-FP908. Color: black, code: PPG AU37-FP908. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear bumper.
ADDITIONAL OPTIONS	Goes with Q#256455.
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s),!Manac will have the obligation to ensure the trailer(s) produced meet!minimum GHG guidelines. Any modifications required to meet the GHG!regulations will be added to the initial purchase price and charged back to!the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.