

# HALE

## TRAILER

### BRAKE & WHEEL



A036118-A036126  
VIN: A7880-A7888

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

Xcalibur Extendable 53ft - 90ft Air Ride Slider Tandem (Model: XCALIBUR XTP5390SA2)	
XCA5390SAXT859492	Est. Wt.: 18,850# +/- 3%
<b>TRAILER - GENERAL</b>	
<b>Capacity:</b> 100,000 lbs distributed - self-supporting, properly blocked	
<b>Length:</b> 53 feet (closed) to 90 feet (open)	
<b>Width:</b> 8 feet 6 inches	
<b>DECK-FRONT</b>	
<b>Kingpin:</b> 24 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM Standard	
<b>Bulkheads:</b> None	
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel	
<b>DECK-MAIN</b>	
<b>Main Beams:</b> Minimum grade 80 flanges	
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers	
<b>Rubrail:</b> 2 1/2 inch x 3/8 inch thick HD mill formed steel	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rub rail	
<b>Flooring:</b> 1 1/8 inch wood	
<b>Winch Track:</b> Full-length steel on road side	
<b>Sliding Winches:</b> 12 - without straps	
<b>Winch Straps:</b> None	
<b>Air and Electrical @ Extension Locks:</b> Inside track system	
<b>Tool Box:</b> None	
<b>DECK-REAR</b>	
<b>Bumper:</b> Meets underride requirements	
<b>Mudflaps:</b> 1 set Fontaine	
<b>AXLES</b>	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Dust Shields:</b> None	
<b>Axle Spread:</b> 49 inches	
<b>WHEELS AND TIRES</b>	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Grease in hubs	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white -	
<b>Tires:</b> 11R 22.5 14PR OEM Standard tires	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
<b>SUSPENSION</b>	
<b>Suspension:</b> Sliding air tandem	
<b>Suspension:</b> Hendrickson air ride on slide box- 96 inches adjustable CAL LEGAL	
<b>ABS:</b> 2S/1M - no cable or tool	
<b>Load Scale:</b> None Standard	
<b>LIGHTING</b>	
<b>Electrical System:</b> Sealed harness and LED Lights: 3 lights per side on rear with 4 inch flush mounted amber strobes (no battery back-up)	

<b>PAINT</b>	
<b>Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001</b>	
<b>MISCELLANEOUS</b>	
<b>VIN Plate: Bilingual VIN plate</b>	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Additional Options:</b>	
<b>Aluminum Air Tank</b>	
<b>Zinc Rich Primer</b>	

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.