

HALE TRAILER BRAKE & WHEEL



A036288-A036308
VIN: S035026-S035406

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Infinity Flat 48' Wide Spread Air (Model Code: HAICF12WSA)

Length / Width: 48 feet x 102 inches
Suspension Type: Wide spread air
Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: 15 pair recessed in siderails
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks, Aluminum Air Tank
Air Line Filters: (2) Meritor In-line type installed
ABS: 2S/1M- no cable or tool
Axle Spread: 122 inches - set at rear
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 4 steel disc inside wheels - 4 aluminum High Polish outside with 4 Spacers
Tires: 11R 22.5 14PR OEM standard tires
Tire Inflation System: None standard
Suspension Detail: Hendrickson AANT23K Intraax air ride
Auto Glad Hand Dump : Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Air Lift: Lift Not Included: *On Front Axle Only Install Hendrickson UBL-401 Front Bolt-on Suspension Hanger Brackets (LH C-32038-1C & RH C-32038-2C), Weld-on Lift Brackets (LH C-28617-1 & RH C-28617-2), & A-30634-1 Bolt Kit; Install Appropriate K-Brace To Fit Around These Brackets (**HALE TRAILER WILL FURNISH AND INSTALL (2) Air Springs in Addition to other required plumbing and Lift axle Control Components)
Front Corners: Tapered steel
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Weld-on type - meets underride requirements - painted steel
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle
Spare Tire Carrier: Spare tire carrier - bolted on curbside
Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD
Sliding Winches: 12 Zinc Finished: 6 each side with Sliding Rope Hook/Winch Strap Hook Retainers Standard; Number of Additional Sliding Winches and Hooks Added to Std. Qty. of 12- EACH - Qty: 2
27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: None standard
VIN Plate: Bilingual US/Canadian VIN plate
Unit Numbers & Decals: Not installed

Estimated Weight (lbs) (+/- 3%)

10,213

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.