

# HALE

## TRAILER

### BRAKE & WHEEL



**A036442-A036456**  
**VIN: S035179-S035139**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

#### Velocity Drop Deck 53' Wide Spread Air (11'-42') (Model Code: HCVSD22WSA)

<b>Overall Length:</b> 53 feet x 102 inches
<b>Suspension Type:</b> Wide spread air
<b>Deck Lengths:</b> 11 feet front and 42 feet rear
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
<b>Rear Deck Height:</b> 40 inches
<b>Flooring:</b> 1 1/8 inch wood
<b>Crossmembers:</b> 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers
<b>Pipe Spools:</b> Double between stake pockets
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM standard
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkheads:</b> Removable Galvanized Steel 4 post NON-DOT bulkhead - no turnback - 48 inches high for use with front pockets
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks, Aluminum Air Tank
<b>Air Line Filters:</b> (2) Meritor In-line type installed
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:</b> 122 inches - set like a 48 foot trailer (Approx. 43 feet C/L KP to C/L rear axle)
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
<b>Tires:</b> 255/70R 22.5 16PR OEM standard
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> AANL23K Intraax air ride
<b>Auto Glad Hand Dump :</b> Installed
<b>Electric Dump Valve:</b> Wired to 7-way auxiliary socket to dump rear axle
<b>Air Lift:</b> None Standard
<b>Front Corners:</b> Tapered
<b>Electrical System:</b> LED: 3 lights/side, 3 lights/side on rear - STANDARD
<b>Paint:</b> Black urethane with Velocity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails
<b>Bumper:</b> Weld-on type - meets underride requirements
<b>Mudflaps:</b> 2 sets OEM standard; Spring loaded brackets behind front axle
<b>Winch Track:</b> Steel on road side: 8-foot front deck and full length on rear deck where possible
<b>Sliding Winches:</b> 12 Zinc Finished Winches: 2 front deck and 10 rear deck
<b>27 foot Winch Straps:</b> None standard
<b>30 foot Winch Straps:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Spare Tire Carrier:</b> 1 standard - mounted between lower gooseneck beams
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate
<b>Unit Numbers &amp; Decals:</b> Not installed

Estimated Weight (lbs) (+/- 3%)

12,520

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.