

# HALE TRAILER BRAKE & WHEEL



A036508-A036513  
VIN: S035245-S035250

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 \*FINANCING AVAILABLE

## Velocity Drop Deck 53' Tridem Air Ride (Model Code: HAVSD22TAF)

**Overall Length:** 53 feet x 102 inches

**Suspension Type:** Tri-axle air

**Deck Lengths:** 11 feet front and 42 feet rear

**Frame Rating:** 100,000 lbs distributed- GAWR and tire ratings determine legal payloads

**Rear Deck Height:** 40 inches - loaded

**Flooring:** 1 1/8 inch wood

**Crossmembers:** 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

**Side Rails:** 6 inch structural channel @ 6.5 lbs/ft - full length on rear deck

**Stake Pockets:** 3/16 inch steel on 24 inch centers

**Pipe Spools:** Double between stake pockets

**Rubrail:** 3/8 inch x 2 1/2 inch steel

**Main Beams:** 130K load bearing flanges

**Kingpin:** 18 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM standard

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkheads:** None standard

**Bulkhead Pockets:** 4 - F-5 DOT-type steel

**Number of Axles:** 3 Intraax

**Axle Position:** Fixed

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks, Aluminum Air Tanks

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 4S/2M - no cable or tool

**Axle Spread:** 60 inches, 60 inches - kingpin to center axle 40 feet 10 7/8 inches

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 22.5 x 8.25 6 steel disc inside wheels - 6 aluminum High Polish outside with 6 Spacers

**Tires:** 255/70R 22.5 16PR - quantity 12 OEM standard

**Tire Inflation System:** Hendrickson TIREMAAX PRO inflation system

**Suspension Detail:** AANL23K Intraax air ride

**Auto Glad Hand Dump :** Installed

**Electric Dump Valve:** Wired to 7-way auxiliary socket to dump rear axle

**Air Lift:** (1) UBL installed on Rear Axle; Includes additional leveling valve to fully raise lower deck when this axle is lifted to try and achieve additional tire ground clearanc; NOTE: Load on 2 Axles not to exceed 20k Each; Fontaine will not be responsible for tire flat spot and/or damage due to rear lifted axle

**Front Corners:** Tapered

**Electrical System:** LED: 7 lights/side, 3 lights/side on rear; add Install Extra Side MARKER LIGHTS - \*Extra Pairs Added & To Be Spaced Between 3 Existing Std. Lights: Total Qty. of Pairs to be Added Are 3

**Paint:** Black urethane with Velocity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed on rubrails

**Bumper:** Weld-on type - meets underide requirements

**Mudflaps:** 1 set OEM standard behind rear axle

**Winch Track:** Steel on road side: Full length where possible

**Sliding Winches:** 16 standard: 3 front deck and 13 rear deck

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Spare Tire Carrier:** 1 standard - mounted between lower gooseneck beams

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

**Unit Numbers & Decals:** Not installed

**Select:** Remove (2) Inner Tail Lights of 3 Light Rear; Install Manual Toggle Switch Connected to Harnesses of Removed Lights; \*Ship Loose (2) 4" Amber Lights To Be Installed By Customer

DISCLAIMER Estimated Weight (lbs) (+/- 3%) 14,321

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.