

HALE TRAILER BRAKE & WHEEL

A036775-A036776
VIN: 66069-66070

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     
800-232-6535 *FINANCING AVAILABLE



PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 14.2 Units

STANDARD SPECIFICATIONS: **CTSSF-45**

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor

Construction: **.063 skin stressed aluminum with aluminum exterior posts on 21.5" centers, bevelled corners**

Unloading Time: Approximately 8 minutes

Capacity: 14.2 units (105 cu yd)

Dimensions: **45' long, 8' 0" wide, 13' 3" high**, 37" king pin location, 36" rear axle from rear of trailer

Tires: Eight (8) **11:00 x 22.5** radial tires

Wheels: Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount

Axles: 22,500# cap. , **71 1/2" track**, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem, (**Hutch H9700T**)

Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**)

King Pin: Standard SAE, heat treated, 37" setting, 51" height, **5/16" plate - 2 beam**

Cross Sills & Decking: Keith 7/32" with wear strips, 3" cylinder, rubber seals, standard live floor, **4" Jr. I-Beams on 22" centers** with aluminum sub-deck, wear strips on one end

Top: Flat design, open top, single center tie

Top Cover: **Shur-lok roll over tarp – with telescoping pole “wil-slip” cap, rear crank - handle holders on both sides – black vinyl - Flat caps**

Tarp Bows: **Ten (10) 3” arched tarp bows (trailer height overall 13’6” w/ 3” arch bows)**

Safety Screens: **Expanded metal over drive and under front**

Rear Door: Full opening, side hinged, **skinned with solid aluminum**

Ladders: One located at front **with safety loop** and one located at rear (**front ladder mounted to headboard**)

Rope Hooks: Furnished

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt

Glad Hands: Standard mounted on road side of headboard

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights **all lights to be LED**

Reflectors: Legal DOT

Paint: Aluminum natural, steel components primed and painted Black

Weight: Approximately 13,420#

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.