

HALE

TRAILER

BRAKE & WHEEL

A036818-A036819 VIN: 187204 & 187209 - Trailer
A036820-A036821 VIN: 187205 & 187210 - Flip Axle
A036822-A036823 VIN: 187206 & 187211 - Flip Axle
A036824-A036825 VIN: 187207 & 187212 - Flip Box
A036853-A036854 VIN: 187208 & 187213 - Spreader

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE



Trailer Model: Single Drop Extendable, Low Profile 60T

Standard Equipment

Net Capacity: 60 Tons in 12' of Closed Deck, 2 Point Load Extended
Nominal Dimension: OAL 53 ft Closed, 74 ft Open & Width 8.5 ft
Capable up to 2-3-2 Configuration

GOOSENECK:

Fixed Narrow Arched Neck
50" Loaded 5th Wheel Height, 18" Setting, 2" King pin
Narrow neck, Chain tray provision in neck's rear
Two position King Pin at 96" & 108" Swing, Front lugs for flip neck
Capable of 60" Flip neck (max) for a total swing of 168"
Landing Gear 2-speed, curbside crank handle.

DECK:

40.5 ft Closed, 61.5 ft Open Length Deck with 8.5 ft Width deck
30" loaded deck ht at rated capacity (Front and rear of lower deck)
Full Depth Cambered Deck Beams
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum
I-Beam Cross members on (approx.) 12" Centers
1 3/8" Nominal Apitong Decking with Open Center
Floor screws used to secure decking on every other cross member

1 Tie Downs per bolster, 1 D ring per Bolster
3/8x2 1/2 rub rail, 24" centers for stake pockets & double pipe spools
Air operated for extendable length with stops approximately 48"

REAR SECTION:

Axles: Three, 5" round, 5/8" wall 25000# nominal capacity
Suspension: Air ride with Oil Seals
60 in. axle spacing, Open wheel wells
Auto Slack Adjusters
12-1/4" X 7-1/2" Air. Parking brakes on all axles
Hub: 10 Stud, Hub Piloted, Long studs, Cast Drums
245/70 R 17.5 Tires on Steel Wheels
Automatic/ Manual ride height control with dump valve & Air Gauge
Air Ride Suspension With adjustable Ride Height
Rear lugs, air & electrical connections for spreader bar & flip axle

GENERAL:

12 Volt System with 7 way Sealed Harness
LED Sealed beam Lights w/ Modular Harness
Strobe light package with toggle switch on rear
Epoxy Primer & Black Polyurethane Paint
Flag and Flag Holders - 2 Pairs - front deck and rear of trailer
Mid-Turn Signal/Clearance Light
KS Mud Flaps Oversize load sign Brackets
Red & White Conspicuity tape

NOTE: Optional Equipment Specifications are on next page

Optional Equipment

☒ Extendable Trailer - 3 Axle 60T, 53-74

Option

☒ 60" Flip Neck
☒ Spreader Bar - 14'1" Nitrogen Assist (Hyd2)
☒ Single Axle Flip
☒ Single Intermediate / Tag axle

☒ 60" Axle Spacing (Ext Deck Length Changes)

☒ Standard Size - 245/70R 17.5 Includes all tires mounted on selected wheels

☒ OEM

☒ Aluminum Outside Wheels all Axles

☒ AirWeigh Load Digital Scale

☒ Tire Inflation System

Estimated Weight of the Equipment with the options :

40,980 lbs.

TANDEM AXLE JEEP:

Capacity - 48K Lbs, 8'6" Wide
King pin at 51" unladen, 50" loaded
96" & 108" Swing for atleast 14' Front Spread
Twin two speed landing gear
Sliding fifth wheel, 48" slide
Lifting & Stacking D rings 2 pair
Axles, Tires and Wheels Match Trailer
Wt. 8,500 lbs +-3%

24" FLIP NECK:

Extension provides 132" swing
Wt. 630 lbs +-3%

SPREADER BAR:

Lugs set up for single axle booster
14' 1" from rear of last trailer axle to booster axle
Two options - Mechanical & Nitrogen assisted
Mechanical System : Wt. 2,830 lbs +-3%
Nitrogen Assisted System: Wt. 6,365 lbs +-3%

60" FLIP NECK:

Extension provides 168" swing
Wt. 2100 lbs +-3%

SINGLE AXLE FLIP:

Capacity - 24K Lbs, 8'6" Wide
Lifting & Stacking D rings 1 pair
Axles, Tires and Wheels Match Trailer
Wt. 3,050 lbs +-3%

INTERMEDIATE SINGLE TAG AXLE:

Capacity - 24K Lbs, 8'6" Wide
Lifting & Stacking D rings 1 pair
Axles, Tires and Wheels Match Trailer
Wt. 3,250 lbs +-3%

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.