

HALE

TRAILER

BRAKE & WHEEL

A036818-A036819 VIN: 187204 & 187209 - Trailer
 A036820-A036821 VIN: 187205 & 187210 - Flip Axle
 A036822-A036823 VIN: 187206 & 187211 - Flip Axle
 A036824-A036825 VIN: 187207 & 187212 - Flip Box
 A036853-A036854 VIN: 187208 & 187213 - Spreader

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE



Trailer Model: **Single Drop Extendable, Low Profile 60T**

Standard Equipment

Net Capacity: 60 Tons in 12' of Closed Deck, 2 Point Load Extended
 Nominal Dimension: OAL 53 ft Closed, 74 ft Open & Width 8.5 ft
 Capable up to 2-3-2 Configuration

GOOSENECK:

Fixed Narrow Arched Neck
 50" Loaded 5th Wheel Height, 18" Setting, 2" King pin
 Narrow neck, Chain tray provision in neck's rear
 Two position King Pin at 96" & 108" Swing, Front lugs for flip neck
 Capable of 60" Flip neck (max) for a total swing of 168"
 Landing Gear 2-speed, curbside crank handle.

DECK:

40.5 ft Closed, 61.5 ft Open Length Deck with 8.5 ft Width deck
 30" loaded deck ht at rated capacity (Front and rear of lower deck)
 Full Depth Cambered Deck Beams
 4 Beam design - 100,000 psi yield flanges & 80,000 web minimum
 I-Beam Cross members on (approx.) 12" Centers
 1 3/8" Nominal Apitong Decking with Open Center
 Floor screws used to secure decking on every other cross member

 1 Tie Downs per bolster, 1 D ring per Bolster
 3/8x2 1/2 rub rail, 24" centers for stake pockets & double pipe spools
 Air operated for extendable length with stops approximately 48"

REAR SECTION:

Axles: Three, 5" round, 5/8" wall 25000# nominal capacity
 Suspension: Air ride with Oil Seals
 60 in. axle spacing, Open wheel wells
 Auto Slack Adjusters
 12-1/4" X 7-1/2" Air. Parking brakes on all axles
 Hub: 10 Stud, Hub Piloted, Long studs, Cast Drums
 245/70 R 17.5 Tires on Steel Wheels
 Automatic/ Manual ride height control with dump valve & Air Gauge
 Air Ride Suspension With adjustable Ride Height
 Rear lugs, air & electrical connections for spreader bar & flip axle

GENERAL:

12 Volt System with 7 way Sealed Harness
 LED Sealed beam Lights w/ Modular Harness
 Strobe light package with toggle switch on rear
 Epoxy Primer & Black Polyurethane Paint
 Flag and Flag Holders - 2 Pairs - front deck and rear of trailer
 Mid-Turn Signal/Clearance Light
 KS Mud Flaps Oversize load sign Brackets
 Red & White Conspicuity tape

NOTE: Optional Equipment Specifications are on next page

Optional Equipment

Extendable Trailer - 3 Axle 60T, 53-74

Option

- 60" Flip Neck
- Spreader Bar - 14'1" Nitrogen Assist (Hyd2)
- Single Axle Flip
- Single Intermediate / Tag axle

60" Axle Spacing (Ext Deck Length Changes)

Standard Size - 245/70R 17.5 Includes all tires mounted on selected wheels

OEM

Aluminum Outside Wheels all Axles

AirWeigh Load Digital Scale

Tire Inflation System

Estimated Weight of the Equipment with the options :

40,980 lbs.

TANDEM AXLE JEEP:

Capacity - 48K Lbs, 8'6" Wide
 King pin at 51" unladen, 50" loaded
 96" & 108" Swing for atleast 14' Front Spread
 Twin two speed landing gear
 Sliding fifth wheel, 48" slide
 Lifting & Stacking D rings 2 pair
 Axles, Tires and Wheels Match Trailer
 Wt. 8,500 lbs +-3%

24" FLIP NECK:

Extension provides 132" swing
 Wt. 630 lbs +-3%

SPREADER BAR:

Lugs set up for single axle booster
 14' 1" from rear of last trailer axle to booster axle
 Two options - Mechanical & Nitrogen assisted
 Mechanical System : Wt. 2,830 lbs +-3%
 Nitrogen Assisted System: Wt. 6,365 lbs +-3%

60" FLIP NECK:

Extension provides 168" swing
 Wt. 2100 lbs +-3%

SINGLE AXLE FLIP:

Capacity - 24K Lbs, 8'6" Wide
 Lifting & Stacking D rings 1 pair
 Axles, Tires and Wheels Match Trailer
 Wt. 3,050 lbs +-3%

INTERMEDIATE SINGLE TAG AXLE:

Capacity - 24K Lbs, 8'6" Wide
 Lifting & Stacking D rings 1 pair
 Axles, Tires and Wheels Match Trailer
 Wt. 3,250 lbs +-3%

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.