

# HALE

## TRAILER

### BRAKE & WHEEL

A036826-A036827 VIN: 187192 & 187198 - Trailer  
 A036828-A036829 VIN: 187193 & 187199 - Flip Axle  
 A036830-A036831 VIN: 187194 & 187200 - Flip Axle  
 A036832-A036833 VIN: 187195 & 187201 - Flip Box  
 A036834-A036835 VIN: 187196 & 187202 - Spreader  
 A036836-A036837 VIN#187197 & 187203 - Jeep Dolly

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE



Trailer Model: **Single Drop Extendable, Low Profile 60T**

#### Standard Equipment

Net Capacity: 60 Tons in 12' of Closed Deck, 2 Point Load Extended  
 Nominal Dimension: OAL 53 ft Closed, 74 ft Open & Width 8.5 ft  
 Capable up to 2-3-2 Configuration

#### GOOSENECK:

Fixed Narrow Arched Neck  
 50" Loaded 5th Wheel Height, 18" Setting, 2" King pin  
 Narrow neck, Chain tray provision in neck's rear  
 Two position King Pin at 96" & 108" Swing, Front lugs for flip neck  
 Capable of 60" Flip neck (max) for a total swing of 168"  
 Landing Gear 2-speed, curbside crank handle.

#### DECK:

40.5 ft Closed, 61.5 ft Open Length Deck with 8.5 ft Width deck  
 30" loaded deck ht at rated capacity (Front and rear of lower deck)  
 Full Depth Cambered Deck Beams  
 4 Beam design - 100,000 psi yield flanges & 80,000 web minimum  
 I-Beam Cross members on (approx.) 12" Centers  
 1 3/8" Nominal Apitong Decking with Open Center  
 Floor screws used to secure decking on every other cross member

1 Tie Downs per bolster, 1 D ring per Bolster  
 3/8x2 1/2 rub rail, 24" centers for stake pockets & double pipe spools  
 Air operated for extendable length with stops approximately 48"

#### REAR SECTION:

Axles: Three, 5" round, 5/8" wall 25000# nominal capacity  
 Suspension: Air ride with Oil Seals  
 60 in. axle spacing, Open wheel wells  
 Auto Slack Adjusters  
 12-1/4" X 7-1/2" Air. Parking brakes on all axles  
 Hub: 10 Stud, Hub Piloted, Long studs, Cast Drums  
 245/70 R 17.5 Tires on Steel Wheels  
 Automatic/ Manual ride height control with dump valve & Air Gauge  
 Air Ride Suspension With adjustable Ride Height  
 Rear lugs, air & electrical connections for spreader bar & flip axle

#### GENERAL:

12 Volt System with 7 way Sealed Harness  
 LED Sealed beam Lights w/ Modular Harness  
 Strobe light package with toggle switch on rear  
 Epoxy Primer & Black Polyurethane Paint  
 Flag and Flag Holders - 2 Pairs - front deck and rear of trailer  
 Mid-Turn Signal/Clearance Light  
 KS Mud Flaps Oversize load sign Brackets  
 Red & White Conspicuity tape

**NOTE: Optional Equipment Specifications are on next page**

#### Optional Equipment

Extendable Trailer - 3 Axle 60T, 53-74

#### Option

- 60" Flip Neck
- Tandem Axle Jeep
- Spreader Bar - 14'1" Nitrogen Assist (Hyd2)
- Single Axle Flip
- Single Intermediate / Tag axle

- 60" Axle Spacing (Ext Deck Length Changes)
- Standard Size - 245/70R 17.5 Includes all tires mounted on selected wheels
- OEM
- Aluminum Outside Wheels all Axles
- AirWeigh Load Digital Scale
- Tire Inflation System

Estimated Weight of the Equipment with the options : **49,490 lbs.**

#### TANDEM AXLE JEEP:

Capacity - 48K Lbs, 8'6" Wide  
 King pin at 51" unladen, 50" loaded  
 96" & 108" Swing for atleast 14' Front Spread  
 Twin two speed landing gear  
 Sliding fifth wheel, 48" slide  
 Lifting & Stacking D rings 2 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 8,500 lbs +-3%

#### SPREADER BAR:

Lugs set up for single axle booster  
 14' 1" from rear of last trailer axle to booster axle  
 Two options - Mechanical & Nitrogen assisted  
 Mechanical System : Wt. 2,830 lbs +-3%  
 Nitrogen Assisted System: Wt. 6,365 lbs +-3%

#### SINGLE AXLE FLIP:

Capacity - 24K Lbs, 8'6" Wide  
 Lifting & Stacking D rings 1 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 3,050 lbs +-3%

#### 24" FLIP NECK:

Extension provides 132" swing  
 Wt. 630 lbs +-3%

#### 60" FLIP NECK:

Extension provides 168" swing  
 Wt. 2100 lbs +-3%

#### INTERMEDIATE SINGLE TAG AXLE:

Capacity - 24K Lbs, 8'6" Wide  
 Lifting & Stacking D rings 1 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 3,250 lbs +-3%

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
 Equipment availability, prices and specifications are subject to change without notice.