

# HALE TRAILER BRAKE & WHEEL



A036897-A036902  
VIN: S035628-S035633

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

### Infinity Low Deck Height Drop Deck 53' Rear Axle Slide Air (Model Code: HAILD22RSA)

**Length / Width:** 53 feet x 102 inches

**Suspension Type:** Rear axle slide

**Deck Lengths:** 11 feet front and 42 feet rear

**Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

**Rear Deck Height:** 36 inches - loaded, 37 inches unloaded

**Flooring:** 1 1/8 inch aluminum with 4 wood nailer strips

**Crossmembers:** 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

**Single Coil Hauling Package:** Included

**Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

**Chain Cargo Tie Downs:** None included

**Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

**Rubrail:** Integrated with siderail

**Main Beams:** 130K load bearing flanges

**Kingpin:** 30 inches

**Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM standard

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front

**Bulkheads:** None standard

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** 12 1/4" X 7 1/2"; Spring brakes; auto slacks; Linings for 20,000# GAWR

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 2S/1M - no cable or tool

**Axle Spread:** 122 inches open - 61 inches closed: Meets California, Canadian RTAC and BC dimensional specifications in closed position

**Hub and Drums:** 8-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 17.5 x 6.75 4 steel disc inside wheels - 4 outside aluminum LVL One Buffed with 4 Spacers

**Tires:** 245/70R 17.5 18PR OEM premium (20,000# GAWR)

**Tire Inflation System:** Hendrickson TIREMAAX PRO inflation system

**Suspension Detail:** Hendrickson HT250US and HTZUS Air Ride

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump :** Installed

**Electric Dump Valve:** Wired to 7-way auxiliary socket to dump rear axle

**Front Corners:** Tapered

**Electrical System:** LED: 5 lights/side, 3 lights/side on rear

**Paint:** Black urethane on steel parts with Infinity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails and rear bumper

**Bumper:** Weld-on type - meets underride requirements - painted steel

**Mudflaps:** 1 set OEM standard behind rear axle only

**Winch Track:** Full length integrated double L type aluminum on both sides where possible -- STANDARD

**Sliding Winches:** 15 Zinc Winches: 6 each side with Sliding Rope Hook/Winch Strap Hook Retainers Standard;

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Spare Tire Carrier:** 1 standard - mounted between lower gooseneck beams at drop

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** 1 CAM LOCK aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side

**VIN Plate:** Bilingual US/Canadian VIN plate

**Unit Numbers & Decals:** Not installed

**Stacking:** Price includes Standard stacking of each trailer

**Air and Electrical:** Install Extra Side MARKER LIGHTS - \*Extra Pairs Added & To Be Spaced Between 3 Existing Std. Lights: Total Qty. of Pairs to be Added Are - Qty: 2

**Estimated Weight (lbs) (+/- 3%) 11,334**

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.