

HALE TRAILER BRAKE & WHEEL



A036903-A036911
VIN: S035634-S035642

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Infinity Drop Deck 53' Wide Spread Air (Model Code: HAICD22WSA)

Length / Width: 53 feet x 102 inches
Suspension Type: Wide spread air
Deck Lengths: 10 feet front and 43 feet rear
Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Rear Deck Height: 40 inches - loaded
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: None included
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges
Kingpin: 18 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM standard
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks, Aluminum Air Tank
Air Line Filters: (2) Meritor In-line type installed
ABS: 2S/1M - no cable or tool
Axle Spread: 122 inches - set like a 48 foot trailer (Approx. 44 foot C/L KP to C/L rear axle)
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 4 steel disc inside wheels - 4 aluminum High Polish outside with 4 Spacers
Tires: 255/70R 22.5 16PR OEM Standard
Tire Inflation System: None standard
Suspension Detail: AANL23K Intraax air ride
Auto Glad Hand Dump : Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Air Lift: None Standard
Front Corners: Tapered
Electrical System: LED: 5 lights/side, 3 lights/side on rear
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Weld-on type - meets underride requirements - painted steel
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle
Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD
Sliding Winches: 15 Zinc Winches total, 3 front deck and 12 rear deck: 8 R/S & 7 C/S; sliding Rope Hook/ Winch Strap Hook Retainers
27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: 1 CAM LOCK aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side between spread axles
VIN Plate: Bilingual US/Canadian VIN plate
Unit Numbers & Decals: Not installed

Air and Electrical: Install Extra Side MARKER LIGHTS - *Extra Pairs Added & To Be Spaced Between 3 Existing Std. Lights: Total Qty. of Pairs to be Added Are - Qty: 2

Estimated Weight (lbs) (+/- 3%) 10,840

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.