

HALE TRAILER BRAKE & WHEEL



A037163-A037168
VIN: S035884-S035889

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Infinity TX Twist-Lock Drop Deck 53' Rear Axle Slide Air (Model Code: HAITX22RSA)

Length / Width: 53 feet x 102 inches

Suspension Type: Rear axle slide

Deck Lengths: 11 feet front and 42 feet rear

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded, 41 inches unloaded

Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: None included

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Fifth Wheel Height: 49 inches

Landing Gear: OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front

Bulkheads: None standard

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks, Aluminum Air Tank

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches open - 61 inches closed: Meets California, Canadian RTAC and BC dimensional specifications in closed position

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 4 steel disc inside wheels - 4 aluminum High Polish outside with 4 Spacers

Tires: 255/70R 22.5 16PR OEM standard

Tire Inflation System: None standard

Suspension Detail: Hendrickson Intraax AANL23K and AAZL23K Air Ride (*Subject to change based upon availability)

Air Assist Slide Box Pins: Standard mount of controls on slider frame

Auto Glad Hand Dump : Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Front Corners: Tapered

Electrical System: LED: 5 lights/side, 3 lights/side on rear

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails and rear bumper

Bumper: Weld-on type - meets underride requirements - painted steel

Mudflaps: 1 set OEM standard behind rear axle only

Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD

Sliding Winches: 15 Zinc Winches: 8 on R/S & 7 on C/S each side with Sliding Rope Hook/Winch Strap Hook Retainers

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Container Locks: Retractable to accept (1) 40 foot container or (2) 20 foot containers

Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

Unit Numbers & Decals: Not installed

Air Axle: Lift Not Included: *On Front Axle Only Install Hendrickson UBL-005 Front Bolt-on Suspension Hanger Brackets (LH C-30293-1C & RH C-30293-2C) & Weld-on Lift Brackets (LH C-30209-1C & RH C-30209-2C); Install Appropriate K-Brace To Fit Around These Brackets (**HALE TRAILER WILL FURNISH AND INSTALL (2) C-23114 Air Springs in Addition to other required plumbing and Lift axle Control Components)

DISCLAIMER

Estimated Weight (lbs) (+/- 3%)

11,909

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.