

HALE

TRAILER

BRAKE & WHEEL

A037533-A037537
VIN: 21421-21425

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

INTERSTATE
TRAILERS, INC.

Interstate model 40DLA - Standard Specification

General description:	40,000 lb. capacity tag-along trailer with beavertail & ramps.	Suspension:	Hutch 9700 multi-point spring with radius rod axle tracking adjustment, 44,000 lb. capacity.
Load capacity:	40,000 lbs. at 65 M.P.H. (G.V.W.R. 47,600 lbs.)	Axles:	(2) 25,000 lb. capacity with oil bath hubs.
Overall length:	30'-0"	Brakes:	12-1/4" x 7-1/2" air with "Wabco" anti-lock braking system and spring parking brakes.
Deck length:	24'-0" (19'-0" flat deck + 5'-0" beavertail)	Wheels:	8 hole, hub piloted steel disc.
Deck width:	8'-6"	Tires:	215/75R17.5, (H)
Deck height:	36" unloaded	Ramps:	60" x 22" wood-filled with spring assist.
Frame construction:	Pierced mainbeam construction with one piece interlocking crossmembers. Mainbeams: W14" x 22 lbs. per ft., grade 50 Hi-tensile. Crossmembers: 6" I-beam x 3.9 lbs per ft., grade 50 Hi-tensile on 22" centers. 3/16" steel fabricated knee bracing on every other x-member. Siderails: C8" x 11.5 lbs. per ft. Grade 50 Hi-tensile.	Jack:	25,000 lb. 2 speed, side crank.
Headboard:	8" channel, full width of trailer.	Hitch:	4 position cast steel pintle eye, 1-5/8" stock, 3" I.D.
Decking:	2" nominal oak secured to crossmembers with 5/16" torque screws.	Tie downs:	(8) heavy duty D-rings, 4 per side.
Standard paint:	Black Urethane (Optional colors available) Rust prohibitive undercoating.	Lights:	12 volt DOT & ICC approved. All lights are LED type and flush mounted in rubber grommets. Wiring is run in flexible neoprene jacket and modular in design. 7 way plug.

Factory Installed Options:

Note: Optional equipment may change standard specifications.

- | | |
|--|---|
| ☒ Paver Package (6' beavertail+ 6' ramps): | ☒ Additional deck length: <u>1</u> |
| ☒ Spare tire & wheel: | ☒ 2 way spring assist on ramps: <u> </u> |
| ☒ Spare tire carrier: | |
| ☒ Dual 2 speed landing gear: | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.