HALE TRAILER BRAKE & WHEEL

A038093-A038100
VIN: S036793-S036800

manac

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	According to the loading model provided by Manac engineers and only this one, strucutral capacity can support 80,000 LBS when open. Please note, this does not concern mechanical parts and they would be overloaded in such a case.
LENGTH	53'-0" closed.
LENGTH	71'-0" opened.
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61" high at front and 34" at the bumper.
DROP HEIGHT	25", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 1/2" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 13 1/2" above suspension.
WEB	1/4" plate full length, 80 000 psi steel.
GOOSENECK	12 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanized. Bolted, 12" c/c. (for bolted construction)
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember. (With galvanized flatbed or crossmembers)
SIDE RAILS	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Galvanized front and rear bolted sills.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, ** bolted ** in web and to crossmember, located each side.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
ENDS	
FRONT RAIL	Formed steel 1/4".
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.

manac

ITEM	DESCRIPTION
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams Grote, tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400.
TURN SIGNAL	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way.
STROBE LIGHTS	Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: REAR
TAIL LIGHTS	Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking. TIREMAAX warning lamp installed on road side front rail.
LANDING GEAR	Holland, Mark V (LGH-4F010), heavy duty, with mounting plate, full galvanized
SAND SHOES	18" x 18". Galvanized.
CRANK	Road side.
BOGIE	
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (6.5), tandem, 60" spread.
LIFT DEVICE	Hendrickson HT-250US (6.5) with Manac center lift. Located at 60" rear of tandem. Controled manually. *** Only 1 1/2" of clearance from the ground if used at rear. *** *** NO WARRANTY ON THE TIRES NOR GROUND AXLES, (FLAT SPOT) ***
U-BOLTS	With nuts at bottom.
SPRINGS	Air.
AXLE(S)	Hendrickson, HN-S50H, 20 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None.
BRAKES	12 1/4" standard, long life H20-HXS Hendrickson lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Haldex S-ABA, automatic, curved, 28 splines, (6").
SEALS	*** Stemco, "Platinum Performance System". Including "Guardian seals, Pro-Torq spindle nuts, Integrated Sentinal hub caps with Synthetic oil, Mobil Delvac 75W-90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 8 studs disc hubs, drums 93 lbs, outboard mount, 275mm B.C., single flange nuts. For dual steel wheels or single wheels.
RIMS	17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts, 4 hand holes.
TIRES	Continental, 235/75 R 17.5 HTL-2 ECO-PLUS 18 ply (31.6") Automatic Tire inflation System Tiremaax.

manac

ITEM	DESCRIPTION
AIR SYSTEM	
GLAD HANDS	Fixed, filter on the third glad hand at front.
AIR VALVES	Meritor Wabco, IABS, 2 sensors 1 modulator.
VALVE(S)	Fast-brake kit.
VALVE	Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table.
CONTROL BOX	Stainless steel
AUTOMATIC TIRE INFLATION	Automatic Tire inflation System Hendrickson Tiremaax PRO. For axles with bearings HM 218248 and HM 212049, dual tires. NOTE: Axles prep. fees included for undressed axle. *** Maximum allowable tire pressure for this device is 120psi *** (tridem application)
VALVE	Quick and brake release valves on air lift. "Automatic Tire Inflation Systems", REMARK: Make sure the system is adjusted to the same tires pressure written on the serial plate.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
WINCHES	Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8").
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
EXTRA MUD FLAPS	Qty: 2, rubber. Located: 1 at front of landing gear in between main frames, to protect the hoses coil, and 1 at front of suspension in between main frames, to protect air boosters.
FINISHING	
PAINT	Galvanized plateform. (no paint)
AXLE(S) PAINTED	Color: grey, code: PPG Q37-939514.
HUBS	Same color as trailer.
WHEELS OR RIMS	Powder top coat white.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
SERIAL PLATE	V.I.N. plate to be stick on an aluminum plate riveted on the frame. (it doesn't stick on galvanized steel)
ADDITIONAL OPTIONS	same as U#241374. Add tire inflation system Estimated weight is 20,005 LBS +/- 3%
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.