



## Hale Trailer Brake & Wheel 038461-038462

### Talbert Manufacturing, Inc.

**Model:** AC-20  
**Capacity in tons:** 20

#### 1. TONGUE

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks  
Tongue 5'-6" with lockable tool box with aluminum diamond plate lid  
Note: Move tool box hinge 4" forward  
Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard  
Electrical receptacle Seven pin connector  
Headboard 8" high full width

#### 2. DECK

Deck section design One piece tongue, main beam and beavertail (cold formed)  
Deck section length 27'-0" (21'-0" flat with 6'-0" beavertail)  
Deck section width 8'-6"  
Loaded deck height 32-1/4"  
Flooring 1-1/2" apitong  
Lash rings 10 total -  
4 each side on flat deck (straight style), 8 total  
1 each side on beavertail (straight style), 2 total  
Mainbeams 12" deep hi-tensile  
Crossmembers 6" deep hi-tensile  
Sidemembers 8" deep hi-tensile  
Beavertail 6'-0" with wood flooring full width  
Ramps 5'-0" with wood flooring with 3 springs per ramp and grab handles

#### 3. RUNNING GEAR

Number of axles 2  
Axle capacity 25,000#  
Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.  
Wheels Steel disc with oil seals (6.75 x 17.5)  
Tires Eight (8) 215/75R17.5 (H) 16PR radials  
Use valve stem extensions on inside wheels  
Suspension 44,800# Hutch spring

#### 4. GENERAL

Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK  
Paint Valspar standard Talbert black  
Additional general specifications Formed step in front of 1st axle both sides of trailer

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.