



A038477-A038488
VIN: S037177-S037188



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
DIMENSIONS LENGTH WIDTH HEIGHT	48'-0" 102", 97" between side rails. Floor, approximately 59 1/2" high at front and 54" at rear.
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	3/8", plug welded structure. 30" from front. 48".
STRUCTURE FLANGES WEB GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES RUB RAILS CORNERS X BRACES	44" c/c frame with "CAMBER". 3/8" x 5", high tensile. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. 1 beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative. Screws 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
ENDS FRONT RAIL BUMPER HEADBOARD POCKETS BUMPER REAR RAIL	Formed steel, bolted. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.) *** Galvanized *** 2 bolted galvanised pockets at front for removable headboard. 2 rubber dock, at the end of rear rail. Formed steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS	7 way (SAE J560). Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.



ITEM	DESCRIPTION
TAIL LIGHTS	Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR	Holland, Mark V (LGS-4F315), with mounting plate & solid axles. ***fully galvanized***
SAND SHOES	10" x 10".
CRANK	Road side.
BOGIE	
BASIC MECHANICAL	
BOGIE	Slider, Intraax AAZNT 46K, Z frame structure, 14 R.H., with "UHMV" slider plastic pads, 4 retainers and 4 pneumatic locking pins "Quik Draw". 48" travel, tandem 49" spread.
MECHANICAL (GROUND AXLES)	
SUSPENSION	Hendrickson INTRAAX AANT-23K, tandem with AAZNT 46K. For axles with bearings HM 218248 and HM 212049.
SPRINGS	Air.
AXLE(S)	LDA, 5 3/4" diameter, 23 000 lbs. capacity.
CAM SHAFTS	28 splines with enclosures, 10" long.
TRACK	77 1/2".
DUST SHIELDS	None (Intraax axles).
BRAKES	16 1/2" standard, long life H20-HXS Hendrickson lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	TSE S-ASA, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Doublecoin, 11 R 22.5 TR100 14 ply (41.0")
AIR SYSTEM	
GLAD HANDS	With filter.
AIR VALVES	Meritor Wabco, IABS, 2 sensors 1 modulator.
VALVE(S)	Automatic blow down valve, WITHOUT control box,
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with moose logo and vertical grooves to reduce spray.
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
WINCHES	Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING	
PAINT	Ready for Galvanized plateform.
BOGIE	One coat of epoxy primer and one acrylic urethane top coats,



ITEM	DESCRIPTION
RETROREFLECTIVE TAPES	Color: GREY metallic, code: Q37-939514.
WHEELS OR RIMS	Axles (wheel end) included. (Tandem).
AXLES	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
V.I.N. PLATE	White (power top coat).
	GREY metallic, code: Q37-939514
	V.I.N. plate to be made of metal. Pre-drill the web prior to galvanizing
ADDITIONAL OPTIONS	same as U#238155 but A/R slider & fully galvanized estimated weight is 11,828 LBS +/- 3%
GALVANIZED CHOICES	Galvanized choices.
PLATFORM	Galvanized platform. (no paint)
	** WARNING: holes parachute shaped required for dripping **
CROSSMEMBERS	Galvanized
FRONT RAIL	Galvanized
SIDE RAIL	Galvanized
REAR RAIL	Galvanized
BUMPER	Galvanized
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.