



A038493-A038495
VIN: S037193-S037195



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, STEEL DROP PLATFORM LEGEND SD
DIMENSIONS	
LENGTH	53'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 41" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	1/2" x 5", 100 000 psi steel, 24" high in center and 16 1/2" above suspension.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	With holes, parachute shaped, to lighten trailer.
CROSSMEMBERS	11 1/4" high, 48" straight behind king pin. I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 16" c/c in gooseneck and the remaining 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Screws.
SIDE RAILS	10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets.
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Reinforcement over tires at rear, steel tubing structure, galvanized (G164), floor full length.
KNEE BRACES	3/16" formed steel plates, galvanized (G164), bolted in web and a crossmembers located each side.
X BRACES	Between main beams, full length.
ENDS	
FRONT RAIL	Formed steel, bolted.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground.
BUMPER	2 rubber dock, at the end of rear rail.
REAR RAIL	Formed steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560).
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light.
FLASHERS	Sealed beams LED, one lamp including side marker and flasher,



ITEM	DESCRIPTION
TAIL LIGHTS	each side at middle point, amber. Sealed beams (Grote DEL #54332) red. Qty: 1 additional each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR SAND SHOES CRANK	Holland, ATLAS 55 (LG4421) 10" x 10". Road side.
BOGIE BASIC MECHANICAL BOGIE	Fixed, for tandem 122" spread.
MECHANICAL (GROUND AXLES) SUSPENSION	Hendrickson INTRAAX AANL-23K (6.5), tandem. N.B.: Winged suspension bracket. For axles with bearings HM 218248 and HM 212049.
SPRINGS	Air.
AXLE(S)	LDA, 5 3/4" diameter, 23 000 lbs. capacity.
CAM SHAFTS	28 splines with enclosures, 10" long.
TRACK	77 1/2".
DUST SHIELDS	None (Intraax axles).
BRAKES	16 1/2" standard, long life H20-HXS Hendrickson lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	TSE S-ASA, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Doublecoin, 255/70 R 22.5 RT500 16 ply (36.6")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE(S)	Fixed. Meritor Wabco, IABS, 2 sensors 1 modulator. Automatic blow down valve, WITHOUT control box,
ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES	One plastic, Betts-PS-1 or equivalent. One set, rubber black with moose and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING PAINT	Shot blasted, one coat of epoxy primer and one acrylic polyurethane top coats Color: black, code: PPG CCA947255-55.
BOGIE	One coat of epoxy primer and one acrylic urethane top coats,



ITEM	DESCRIPTION
RETROREFLECTIVE TAPES	Color: black, code: PPG CCA947255-55. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
WHEELS OR RIMS AXLES	White (powder top coat). Color: black, code: PPG CCA947255-55.
ADDITIONAL OPTIONS	same as U#234091
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
DISCLAIMER Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.	