



A038504-A038518
VIN: S037204-S037218



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, STEEL DROP PLATFORM LEGEND SD
DIMENSIONS	
LENGTH	48'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 41" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	3/8" x 5", 100 000 psi steel, goose neck section.
WEB	1/2" x 5", high tensile, 24" high in center and 16 1/2" above suspension.
GOOSENECK	1/4" plate in king pin area and the remaining in 3/16",
CROSSMEMBERS	80 000 psi steel. 24" high, with holes, parachute shaped, to lighten trailer.
FLOOR	11 1/4" high, 48" straight behind king pin.
FLOOR FASTENING	I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised,
SIDE RAILS	16" c/c in gooseneck and the remaining 12" c/c.
SIDE BOXES	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
RUB RAILS	Screws.
CORNERS	10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.
FENDERS	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions).
KNEE BRACES	Cargo pockets.
X BRACES	3/8" x 2 1/2" shaped steel.
ENDS	Bevelled.
FRONT RAIL	Reinforcement over tires at rear, steel tubing structure, galvanized (G164),
BUMPER	floor full length.
HEADBOARD	3/16" formed steel plates, galvanized (G164), bolted in web and a
POCKETS	crossmembers located each side.
BUMPER	Between main beams, full length.
REAR RAIL	Formed steel, bolted.
ELECTRICAL	CMVSS 223-RIG approved (in accordance with Canada & USA regulation).



ITEM	DESCRIPTION
FRONT CONNECTOR	7 way (SAE J560).
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light.
FLASHERS	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
TAIL LIGHTS	Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR	Holland, Mark V (LGS-4F315), with mounting plate & solid axles. ***fully galvanized***
SAND SHOES	10" x 10".
CRANK	Road side.
BOGIE	
BASIC MECHANICAL	
BOGIE	Fixed, for tandem 122" spread.
MECHANICAL (GROUND AXLES)	
SUSPENSION	Hendrickson INTRAAX AANL-23K (6.5), tandem. N.B.: Winged suspension bracket. For axles with bearings HM 218248 and HM 212049.
SPRINGS	Air.
AXLE(S)	LDA, 5 3/4" diameter, 23 000 lbs. capacity.
CAM SHAFTS	28 splines with enclosures, 10" long.
TRACK	77 1/2".
DUST SHIELDS	None (Intraax axles).
BRAKES	16 1/2" standard, long life H20-HXS Hendrickson lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	TSE S-ASA, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 255/70 R 22.5 HSR2 SA 16 ply (36.6")
SPARE TIRE(S)	Doublecoin, 255/70 R 22.5 RT500 16 ply (36.6")
AIR SYSTEM	
GLAD HANDS	With filter.
AIR VALVES	Meritor Wabco, IABS, 2 sensors 1 modulator.
VALVE(S)	Automatic blow down valve, WITHOUT control box,
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with moose logo and vertical grooves to reduce spray.



ITEM	DESCRIPTION
SLIDING TRACK WINCHES	Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING PAINT FINISHING PAINT BOGIE RETROREFLECTIVE TAPES WHEELS OR RIMS AXLES V.I.N. PLATE	Trailer not painted and no primer applied. Galvanized plateform. (chassis) (no paint) Galvanized Siderails, front sill, and rear sill No paint or primer applied One coat of epoxy primer and one acrylic urethane top coats, Color: GREY metallic, code: Q37-939514. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. White (powder top coat). Color: GREY metallic, code: Q37-939514. V.I.N. plate to be made of metal. Pre-drill the web prior to galvanizing
ADDITIONAL OPTIONS	same as 237870 but 122" spread & galvy
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
DISCLAIMER	
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.	