

HALE

TRAILER

BRAKE & WHEEL



A038669-A038670
VIN: 509601-509602

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

GVWR: Trailer to meet 68,000 Pound GVWR
VIN PLATE: US - VIN Plate to Read in English (Standard)
Product Type: HT HyCube

Material no.: 30024926

GEOMETRY

Length - Exterior: 53'-0"
** Length - Interior: 52'-2"
Width - Exterior: 102.36"
** Width - Interior: 101"
* Height - Exterior: 13'-0"
* Height - Interior: 104" Nominal
Deck Height: Standard application
Fifth Wheel Height: 47"
King Pin Location: 36"
Landing Gear Location: 107" from King Pin (+ 1"/-1/4")

TIRES & WHEELS

Tire Furnished: Factory Furnished
* Tire Manufacturer: Bridgestone R-123(G), Low Rolling Resistance Tire
Tire Size: 295/75R22.5
Wheel Furnish: Factory Furnished
Wheel Material: All Steel Wheel
Wheel Manufacturer: HT Standard (TCC 361)
Wheel Size: 8.25 x 22.5, 5-Hand Hole/10 Stud Holes (Steel, Inner & Outer)
* Wheel Finish for Steel: Hot Dip Galvanized.
Tire Stem Valve Position: Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum: None (Due to All Steel Wheel Application)
* Valve Stem & Cap: TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

UPPER COUPLER

Approach Plate: 7/32" THICK 80,000 LB YIELD - 6 SUPPORT CHANNELS
King Pin (BTM Main) Plate: 1/4" thick 80,000 Lb Yield
King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin
Front Bottom Rail: Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y: (1) Tubing Application - Joggled
* Front Bottom Rail External Routing Holes: 1 Slot Hole for Harness and Hoses External Routing

BODY/BASE

Forward Crossmember: Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L
Running Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'
Slider Body Rail (VT): 208" Rail Length
Slider Rail Supplier: Hutchens Slider Rails

FLOOR

Upper Coupler Type: 3.40" Joggled with Exposed Coupler Top Plate (New STD)
Floor Specification: 1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood

Floor Ratings - VT:	18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating
Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

FRONT

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
* Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid (Bottom Open)
* Front Receptacle(7-Way):	Phillips 7-Way Without Circuit Breakers, Split Pins w/Q-BOX 16-8510
* Gladhand/7-Way Location:	(Exterior Harness Routing) Overlaid on Lower Roadside Front (STD) - Mounted on external overlaid HDG mounting bracket
* Corner Radius Protector:	(2) 0.125" X 12" SMOOTH Alum Each Side at Top

SIDE

Side Material:	0.05" Aluminum Prepainted White w/ natural color rivets
Side Posts:	0.45" Deep 14 Gauge Galv Steel "A" Slotted Logistic Posts
* Side Post Centers:	12" C/L Full Length
Side Top Rail:	Shallow Post Side Top Rail
Side Bottom Rail:	Side Bottom Rail STD
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

REAR

* Rear Frame:	Roll-Up Door, 6" Roll-Up Header (New Open Design)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
* Dry Van -WHITING RU:	Whiting Roll-Up Door. STD 3/4" Prepainted White Plastic Face Plywood
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
* Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal
* Option - Horiz Member/Other:	Construction of two pieces standard stitch welding
Underide Bolt Spec.:	Geomet bolts & nuts - Standard
* Dock Bumper:	None (Preparation For Future Lift Gate Installation). Delete "Eyebrow" Around Tail Lights
* Track Protector:	10Ga x 48" High Galvanized Steel Roll-Up Door Track Protector
* Door Accessories:	Roll Up Door Standard Door Components
Rear Frame Design:	Rear Frame Open Door Sill New Design

LIFT GATE

* Lift Gate Furnish:	Factory Furnished
* Lift Gate Type:	Column
* Lift Gate-Mounting Method:	Bolt On - Column
** Lift Gate-Spec Maxon Column:	BMRB-44G,ST84X85"+ 16"ARR+ w/Galv steel Platform/Gravity Down/Bolting Type/20'KIT
Comment: Reference Maxon Quote #132435	
* Lift Gate-Detail Spec:	Install Lift Gate Manufacturer'S Standard Components
* Lift Gate-Battery:	Factory Furnish and Install (2) Liftgate Batteries
* Lift Gate-Battery Detail Spec:	HT Standard (Interstate) Liftgate Batteries
* Lift Gate-Battery Charger Spec:	Single & Dual Pole Receptacle w/Nose Box
* Trail Charger Location:	Connected & above Front 7-Way Box
* Lift Gate-Additional Option:	Install (Or, Prep for Future Install) Lift Gate Manufacturer's Standard Components

ROOF

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

LANDING/SCUFF

Side Lining:	0.235" HDPE Recycled Plastic Installed between Posts
Front Lining:	0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height
* Base Side Scuff:	0.63" x 12" High White Recycled Plastic
Side Scuff Band Mounting Method:	Mounted Directly to Posts
* Front Scuff:	0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)
* Logistic Track:	(2) Row of "E" Track, Galvanized - Overlaid, Both Side
** Logistic Track Location:	Located at 27" & 56" Floor to Centerline of E Track
* Logistic Track Installation:	Standard Installation
Front Corner Lining Support:	Galv Steel Front Corner Liners

LANDING GEAR

L/Gear Spec.:	Jost HT421.G3.17.157 5 Year Warranty Full HDG
L/Gear Mt'g Method:	Inboard Mounting (Standard)
L/Gear Shoes:	10" X 10" RCF (Removable Cushion Foot) Low Profile
L/Gear Ground Clearance:	Nom. 12" Ground Clearance
L/Gear Mt'g Bracket:	Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle:	Roadside
* L/Gear Options:	Fabricate and Install Spill Kit Bracket by landing gear legs Including (2) chain "come-along" device for storage
L/Gear Cross Brace Design:	HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type:	Sliding Tandem(2) Axle Bogie
Axle Spacing:	49" Axle Spacing
Axle ABS System:	Tandem Axle w/2S1M ABS System
Bogie & Axle Location:	Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
Option-Related Bogie Stopper Feature:	STD plug stopper
Susp. Manufacturer:	Hendrickson
Suspension Capacity:	Standard Duty
* Hendrickson Susp. Specification:	Hendrickson Vantraxx HKANT40K Air Ride
Surelok (Anti-Dock):	Surelok (Anti-Dock) Installed
Locking Pin Mechanism:	Air-Assist Pin Puller or Quik Draw
* Susp. Sub-Frame:	Hendrickson K-2 STD Duty (Vantraxx, Intraxx)
* Air System & Suspension Accesories:	Right Weight Load Scale in Weather Proof Box Located Forward of Slide Rail
Type of Susp Spring:	Air Bag
Spring Specification:	Air Bag
Axle Diameter:	5.75"
Axle Supplier:	Hendrickson
Axle-General Spec.:	Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Tapered Spindle
Axle Configuration:	Axle included in Suspension
Brake Lining Size:	16.5" X 7" Drum Brakes
Brake Lining Spec.:	Hendrickson Extended Service H20
Brake Control System:	2S/1M Wabco iABS
Spring Brake Control:	Sealco 110500 Springbrake Priority
Brake Cont-Hose & etc.:	Standard Air Line & Hose Application (US&Canada)
Slack Adjuster Spec.:	TSE Slack Adjuster Part # TSE07135S. Auto-5.5#, 28 Spline
Brake Chamber Spec.:	TSE 3030 Tamper Resist (HT standard)
Stroke Length:	MFG's Standard Stroke Length
Hub Specification:	Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083937, Tapered Spindle
Drum Specification:	Conmet Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco

* Lubrication Spec.:	Chev Delo (Syn) Grease
* Wheel Seals Spec.:	Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
* Hubodometer:	Stemco Hubodometer, Bracket Mounted, Reading in Miles
* Hubodometer Location:	Curbside (RH) Front Axle
* Tire Inflation Spec.:	Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
Tire Inflation Pressure:	100 PSI
* Tire Inflation Lamp Location:	Indicator PSI Light at Roadside Mounted at 24.6" from bottom of front panel over corner radius. (STD location)
* Tire Inflation Lamp Spec.:	33 Series Lamp

ELECTRICAL

* Harness-General Spec.:	Molded Color Code Phillips Harness (Sta-Dry)
Harness-Special Feature:	Manufacturer's Standard Feature
* Front Light:	(2) Grote 49333 Yellow Round LED MicroNova Mounted with Grommet
* Rear ID Header Light:	(5) Grote 49362 Red Round LED MicroNova Dual Function (Cluster of 3 & 1 Each Outboard)
Rear ID-Special Feature:	Dual Function Rear Header Lights: 3 center marker lamps with stop function, and 2 outboard marker lamps with turn function
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
* Rear Side Marker Detail Spec:	(2) Grote 49322 Red Round LED MicroNova w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
* S/T/Tail Light-Quantity & Type:	(4) Grote 53 Series-Round Style (40 Series, Round Style) or Equivalent
* S/T/Tail Light-Detail Spec:	(4) Grote 53272R LED(Round Style-40 Series) Gray Flange Mounted w/stainless steel rivets
Main Mid-Turn Light:	Install the Mid turn lamp
Mid-Turn Mounting Method:	Mounting Bracket
* Main Mid-Turn Light-Detail Spec:	(2) Grote 54143Y Oval SuperNova LED with Oval theft resistant flange bracket 43220
* ABS Light Detail Spec:	(1) Grote 49333 LED MicroNova PC Rated with Adjacent ABS Decal
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
* License Light:	(1) Grote 60711 LED DOT Micronova
* Dome Lamp-Spec.:	Phillips 51HY26654 Rectangular LED Dome Lights
* Dome Lamp-Quantity:	Install (3) Three
* Dome Lamp-Location:	Evenly Spaced at C/L of Ceiling to swing door trailers
* Dome Lamp Switch:	Recessed Toggle Switch at Lower Rear Curbside & Pressure Switch-Tramec 38046X (HT STD)
* Dome Lamp Circuit Connection:	Black Circuit: Power from Clearance, Sidemarker & ID lamps
* Pressure Switch Location:	Inside Upper Coupler
Option Related Harness/Wiring:	Standard
Electrical Related Regulation:	Standard Application

MARKING/DECALS

* HT & Product Type Decal Package:	Delete All Hyundai Logos
* Decal Package:	Customer Furnished Owner Decal Package, Specified in Notes
* Decal Opt 1-Additional Decal:	Specified in Notes
Comment:	Install Customer Furnished Republic Services Decals per Decal Schematic
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
Conspicuity Vendor:	3M
* Conspicuity Markings:	Hyundai Standard Conspicuity without Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
* Furnish Manifest Box:	Factory Furnished
* Manifest Box Detail Spec:	(1) James King #200

- * Document Holder/Manifest Loc.: Document Holder Overlaid on Lower R/S Front, 18" from the bottom of the front sheet.
Manifest Box Overlaid on Lower R/S Front above Document Holder
- Warning Decal Install Instruction: HT standard installation

PAINT/FINISH

- Upper Coupler Finish: Galvanized-Whole upper coupler section
- Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
- Axle & Components Finish: Black Undercoating
- Susp. Sub-Frame Finish: Black Undercoating
- L/Gear(K-Bracing) Finish: Hot Dip Galvanized
- L/Gear(Upper Leg) Finish: Hot Dip Galvanized
- Rear Frame-Finish: Hot Dip Galvanized
- Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)
- Rear Underride-Finish & Spec.: Hot Dip Galvanized & Welded Horizontal Member
- Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

MISCELLANEOUS

- Mudflap Provider: Factory Furnished Mudflaps
- ** Mudflap Specification: 24"x30" White Plain Plastic with NO Logo 3/8# thick with Anti-spray ribs
- * Mudflap Mounting Location: Suspension frame (Tandem/Single axle frame without P.H.)
- * Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer
- * Mudflap Bracket design: 1 Piece Bracket
- * Lift Pad Spec.: Install HT Occasional use lift pads for delivery
- * GPS or ID Supplier: Customer Furnished
- * GPS or ID Specification: Samsara GPS Asset Gateway-AG52
- * GPS or ID Install/Instruct: Standard installation per Mfg's suggestion
- * Import export Decals: With HYUZ Decals

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.