

HALE

TRAILER

BRAKE & WHEEL



A038706-A038720
VIN: 510001-510015

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

GVWR

* GVWR:	Trailer to meet 80,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT Combo Latitude

Material no.: 30024928

GEOMETRY

* Length - Exterior:	53'-0"
Width - Exterior:	102.36"
Fifth Wheel Height:	47"
* King Pin Location:	30"
* Landing Gear Location:	108" from King Pin (+ 1"/-1/4")
Latitude Front Deck Height:	59-3/4" ($\pm 1/2"$)
Latitude Rear Deck Height:	54-5/16" ($\pm 1/2"$)

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
* Tire Size:	11R22.5
Wheel Furnish:	Factory Furnished
* Wheel Material:	Inner Steel & Outer Aluminum Wheel
* Wheel Manufacturer:	HT Standard (TCC 361) Steel Inner & Alcoa Aluminum Outer
* Wheel Size:	8.25 x 22.5, 10(Al) 5(Steel) Hand Hole, 10 Stud Holes (Steel Inner & Aluminum Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
* Wheel Finish for Aluminum:	Aluminum Disc Outer Mill Finished and Inner Steel Disc
* Wheel Accessories:	Install Wheel Separator (Spacer) between Wheels
* Valve Stem & Cap:	Myers TR-572-F19 Valve stem

UPPER COUPLER

* Approach Plate:	5/16" Thick 50,000 PSI Yield (Duralite)
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin

DURALITE OPTIONS

* Cross Members:	4" Steel I-Beams : 12" C/L & Short 6" C/L @Middle 4' of Trailer Bay Area (Coil Package)
* Main Web:	3/16" Thick. Welded One Piece Type (80 KSI)
Top Flange:	3/8" Thick, 110 KSI Domex, 5" Wide One Piece Type
* Bottom Flange:	1/2" Thick, 100 KSI Domex, 5" Wide One Piece Type
* Main Beam - Options:	Belly-Shaped Design
* Gusset Type:	Triangle Type
Gusset Specification:	(3) on Each Side (HT STD)
* Front Sill:	3/16" Steel for HT Aluminum Side Sill
* Front Stake Pockets:	4 EA for Steel Bulkhead Installation
* Bulkhead Specification:	For Future Bulkhead Installation
* Rear Sill:	HT 9# Aluminum Extrusion
* Side Rail:	HT Integrated Aluminum High Impact Side Rail
Winch Rail:	Integrated Aluminum Winch Rail with Side Rail
* Winches:	Sliding Galvanized Steel Winches, (7) on Each Side.
Sliding Winch Stoppers:	Stoppers at Front and Rear (Flatbed STD for Sliding Winches)

* Main - Options:	Install Tire Carrier. One (1) Mounted Curb Side Behind Landing Gear (STANDARD). Rear step Ladder with handle integrated.
Fastener Options:	Standard Fasteners
* Tool Box:	(1) Aluminum Toolbox - 24X24X60 Double Door with Locking Rod
* Tool Box Location:	Road Side, Center of Trailer

FLOOR

Duralite Floor Specification:	1-1/8" Aluminum with 4 Apitong Nailer Strips (Combo STD)
Floor Screws:	HT Duralite Standard (2 Screws Per Board on I-beams)

FRONT

Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid Straight Type
Front Receptacle(7-Way):	HT Duralite Standard (Phillips 7-Way Integrated with Main Harness)
Gladhand/7-Way Location:	(Interior Harness Routing) Overlaid on Lower Centerline Front

REAR

Rear Underride Guard:	4" Tube Bolt on Assembly w/ Bolt on Perforated(Poched) Horizontal
Dock Bumper:	Pair Heavy Duty Dock Bumper (Ref. Buyers B4500)
Rubber Bumper Location:	HT Duralite Standard Location

LANDING GEAR

* L/Gear Spec.:	JOST 450-T-17 Magnum 10 Year Warranty(For Duralite)
L/Gear Shoes:	10" X 10" X 4" Sand Shoe (HT Duralite STD)
L/Gear Crank Handle:	Roadside
* L/Gear Cross Brace Design:	Heavy Duty Cross Brace and attachment Design

RUNNING GEAR

* Bogie Type:	Fixed Single(1) Axle@Front & Sliding Single(1) Axle@Rear
* Axle Spacing:	61" Closed and 122" Opened
Axle ABS System:	Tandem Axle w/2S1M ABS System
* Duralite Bogie & Axle Location:	Fixed Front Axle & Sliding Rear Axle. Meet 40# KPRA to CA Regulation in Close Position
Susp. Manufacturer:	Hendrickson
Suspension Capacity:	Standard Duty
* Duralite Susp. Specification:	Hendrickson AAT23K Air Ride + AAZNT23K Air Ride
Surelok (Anti-Dock):	No Surelok (No Anti-Dock)
* Susp. Dump Valve:	Auto Dump Valve with Meritor Single Tag Axle Dump
Locking Pin Mechanism:	Air-Assist Pin Puller or Quik Draw
Type of Susp Spring:	Air Bag
Spring Specification:	Air Bag
Axle Supplier:	Hendrickson
Axle-General Spec.:	Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Parallel Spindle
Brake Lining Size:	16.5" X 7" Drum Brakes
Brake Lining Spec.:	Hendrickson Extended Service H20
* Brake Control System:	2S/1M Wabco iABS Premium
Spring Brake Control:	Sealco 110500 Springbrake Priority
Drain Valve & Other:	Parker DC604-4 Drain Cock
* Slack Adjuster Spec.:	TSE Slack Adjuster Part # TSE07135S. Auto-5.5#, 28 Spline
Brake Chamber Spec.:	TSE 3030 Tamper Resist (HT standard)
Stroke Length:	MFG's Standard Stroke Length
* Hub Specification:	Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083939, Parallel Spindle
* Drum Specification:	Conmet Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
Lubrication Spec.:	Chev Delo Gear EP5 80-90 oil
Wheel Seals Spec.:	Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut
Air Tank Vendor:	Hoosier Steel Air Tank

ELECTRICAL

* Harness-General Spec.:	Molded Color Code Phillips Harness (Sta-Dry) with Locking Device connector
Harness-Special Feature:	Manufacturer's Standard Feature
* ID/Marker Light Spec:	(3) Phillips 3/4" Penny ID / Marker Light & Anti-theft (with locking device connector)
* S/T/Tail Light-Detail Spec:	(6) Phillips 51-HY40202 4" Round STT w/Flange-Red (3 on each side)
* Main Mid-Turn Light-Detail Spec:	(2) Phillips 51-HY60303-0 LED 6.5" Oval MidTurn/Marker - Amber Surface Mount with Stainless Steel Cover Ring 51-60904
* ABS Light Detail Spec:	(1) Phillips 51-HY37323 Amber 3/4" Penny, PC Rated w/anti-theft hardware
* License Light:	(1) Phillips 51-HY37721-0 (Button Style, Clear) with Grommet (19mm Hole Required)

MARKING/DECALS

Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
* License Plate Brk't Install:	License plate to be installed on R/S (Duralite)
* Duralite Decal - Options:	COIL PACKAGE LOCATION DECAL
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front only for Reefer product type

PAIN/FINISH

Axle & Components Finish:	Black Undercoating
* Susp. Sub-Frame Finish:	Hot Dip Galvanized Duralite Fixed Suspension & Black undercoating for sliding suspension.
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
L/Gear(Upper Leg) Finish:	Black Undercoating
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Bolted Horizontal Member
Duralite Product Finish:	Hot Dip Galvanized

MISCELLANEOUS

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x24" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Method/Install:	STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.