HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A038916-A038918
VIN: A8038-A8040

Quote Number: 3015017
Serial Number: A8038-A8040

Xcalibur Extendable 53ft - 90ft Air Ride Slider Tandem (Model: XCALIBUR XTP5390SA2)	
XCA5390SAXT859492	
	Est. Wt.: 18,850# +/- 3%
TRAILER - GENERAL	
Capacity: 100,000 lbs distributed - self-supporting, properly blocked	
Length: 53 feet (closed) to 90 feet (open)	
Width: 8 feet 6 inches	
DECK-FRONT	
Kingpin: 24 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Bulkheads: None	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
DECK-MAIN	
Main Beams: Minimum grade 80 flanges	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Rubrail: 2 1/2 inch x 3/8 inch thick HD mill formed steel	
Conspicuity Tape: Per NHTSA specs - installed on rub rail	
Flooring: 1 1/8 inch wood	
Winch Track: Full-length steel on road side	
Sliding Winches: 12 - without straps	
Winch Straps: None	
Air and Electrical @ Extension Locks: Inside track system	
Tool Box: None	
DECK-REAR	
Bumper: Meets underride requirements	
Mudflaps: 1 set Fontaine	
AXLES	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Dust Shields: None	
Axle Spread: 49 inches	
WHEELS AND TIRES	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white -	
Tires: 11R 22.5 14PR OEM Standard tires	
Hubodometer: None Standard	
Tire Inflation: None Standard	
SUSPENSION	
Suspension: Sliding air tandem	
Suspension: Hendrickson air ride on slide box- 96 inches adjustable CAL LEGAL	
ABS: 2S/1M - no cable or tool	
Load Scale: None Standard	
LIGHTING	
Electrical System: Sealed harness and LED Lights: 3 lights per side on rear with 4 inch flush mounted amber strobes (no battery back-up)	

PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	
Additional Options:	
Aluminum Air Tank	

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.