



A038921-A038935  
VIN: 243270-243284



SALES | RENTALS | PARTS | SERVICE

|                   |              |                  |              |
|-------------------|--------------|------------------|--------------|
| Allentown, PA:    | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD:    | 888-601-7500 | Portland, ME:    | 800-325-4253 |
| Concord, NC:      | 800-438-2250 | Raleigh, NC:     | 833-418-9777 |
| Delmar, DE:       | 866-486-1400 | Scranton, PA:    | 800-569-1400 |
| Des Moines, IA:   | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD:       | 800-544-7127 | Voorhees, NJ:    | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA:     | 800-854-5310 |

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

| ITEM              | DESCRIPTION                                                                                                                                                                                                           |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE              | SEMI-TRAILER, STEEL PLATFORM LEGEND SD                                                                                                                                                                                |
| DIMENSIONS        |                                                                                                                                                                                                                       |
| LENGTH            | 53'-0"                                                                                                                                                                                                                |
| WIDTH             | 102", 97" between side rails.                                                                                                                                                                                         |
| HEIGHT            | Floor, approximately 59" high at front and 52" at rear.                                                                                                                                                               |
| COUPLING          |                                                                                                                                                                                                                       |
| COUPLER PLATE     | 3/8", plug welded structure.                                                                                                                                                                                          |
| KING PIN LOCATION | 30" from front.                                                                                                                                                                                                       |
| COUPLER HEIGHT    | 48".                                                                                                                                                                                                                  |
| STRUCTURE         | 44" c/c frame with "CAMBER".                                                                                                                                                                                          |
| FLANGES           | 1/2" x 5", 100 000 psi steel.                                                                                                                                                                                         |
| WEB               | 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel, with holes, parachute shaped, to lighten trailer.                                                                                           |
| GOOSENECK         | 11 1/4" high, with integrated nose ramp and 48" straight behind king pin.                                                                                                                                             |
| CROSSMEMBERS      | 1 beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c.                                                                                                                                                      |
| FLOOR             | Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.                                                                                                                                                |
| FLOOR FASTENING   | Screws                                                                                                                                                                                                                |
| SIDE RAILS        | 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.                                                                                                                                                         |
| SIDE BOXES        | 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets.                                                                                                                                |
| RUB RAILS         | 3/8" x 2 1/2" shaped steel.                                                                                                                                                                                           |
| CORNERS           | Bevelled.                                                                                                                                                                                                             |
| X BRACES          | Between main beams, full length.                                                                                                                                                                                      |
| ENDS              |                                                                                                                                                                                                                       |
| FRONT RAIL        | Formed steel, bolted.                                                                                                                                                                                                 |
| BUMPER            | CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground. |
| HEADBOARD         | 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.)<br>*** Galvanized ***                                          |
| POCKETS           | 2 bolted galvanised pockets at front for removable headboard.                                                                                                                                                         |
| BUMPER            | 2 rubber dock, at the end of rear rail.                                                                                                                                                                               |
| REAR RAIL         | Formed steel.                                                                                                                                                                                                         |
| ELECTRICAL        |                                                                                                                                                                                                                       |
| FRONT CONNECTOR   | 7 way (SAE J560).                                                                                                                                                                                                     |
| ELECTRICAL SYSTEM | Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.                                                                                                                                               |
| MAIN SYSTEM       | Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light.                                                                                            |
| FLASHERS          | Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.                                                                                                                       |
| TAIL LIGHTS       | Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking,                                                                                       |



| ITEM                                                                                                                                                                                                                        | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                             | brake with parking.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| LANDING GEAR<br>SAND SHOES<br>CRANK                                                                                                                                                                                         | Holland, Mark V (LGS-4F315), with mounting plate, solid axles.<br>10" x 11 1/2"<br>Road side.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| BOGIE<br>BASIC MECHANICAL<br>BOGIE                                                                                                                                                                                          | Slider, Intraax AAZNT 46K, Z frame structure, 14 R.H., with "UHMV" slider plastic pads, 4 retainers and 4 pneumatic locking pins "Quik Draw".<br>48" travel, tandem 49" spread.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| MECHANICAL (GROUND AXLES)<br>SUSPENSION<br><br>SPRINGS<br>AXLE(S)<br>CAM SHAFTS<br>TRACK<br>DUST SHIELDS<br>BRAKES<br>BEARINGS<br>SLACK ADJUSTERS<br>SEALS<br>BRAKE CHAMBERS<br><br>HUBS AND DRUMS<br><br>RIMS<br><br>TIRES | Hendrickson INTRAAX AANT-23K, tandem with AAZNT 46K.<br>For axles with bearings HM 218248 and HM 212049.<br>Air.<br>LDA, 5 3/4" diameter, 23 000 lbs. capacity.<br>28 splines with enclosures, 10" long.<br>77 1/2".<br>None (Intraax axles).<br>16 1/2" standard, long life H20-HXS Hendrickson lining.<br>HM 218248 and HM 212049.<br>TSE S-ASA, automatic, 28 splines.<br>Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.<br>T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4").<br>(4 years warranty by T.S.E. for parts only).<br>10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts.<br>For dual aluminum wheels.<br>22.5 x 8.25, disc (10 holes),<br>285.75mm B.C., single flange nuts, 2 hand holes.<br>Doublecoin, 11 R 22.5 TR100                      14 ply      (41.0") |
| AIR SYSTEM<br>GLAD HANDS<br>AIR VALVES<br>VALVE(S)                                                                                                                                                                          | With filter.<br>Meritor Wabco, IABS, 2 sensors 1 modulator.<br>Automatic blow down valve, WITHOUT control box,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| ACCESSORIES<br>REGISTRATION HOLDER<br>MUD FLAPS<br>SLIDING TRACK<br>WINCHES                                                                                                                                                 | One plastic, Betts-PS-1 or equivalent.<br>One set, rubber black with moose and vertical grooves to reduce spray.<br>Full length, "LL" extruded aluminum, road side.<br>Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| FINISHING<br>PAINT<br><br>BOGIE<br><br>RETROREFLECTIVE TAPES                                                                                                                                                                | Shot blasted, one coat of epoxy primer and one acrylic polyurethane top coats<br>Color: black, code: PPG CCA947255-55.<br>One coat of epoxy primer and one acrylic urethane top coats,<br>Color: black, code: PPG CCA947255-55.<br>Conspicuity striping in compliance with CMVSS 108. Gray and red each side,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |



| ITEM                                                                                                                                                                                                                                                                                                   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHEELS OR RIMS<br>AXLES                                                                                                                                                                                                                                                                                | fully covers rear sill and horizontal underride protection bar.<br>White (powder top coat).<br>Color: black, code: PPG CCA947255-55.                                                                                                                                                                                                                                         |
| ADDITIONAL OPTIONS                                                                                                                                                                                                                                                                                     | ref. U#238155 but A/R slider, painted and 53' length<br>Estimated weight is 13,082 LBS +/- 3%                                                                                                                                                                                                                                                                                |
| CONFORMITY                                                                                                                                                                                                                                                                                             | This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer. |
| <div>DISCLAIMER</div> <div>Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.<br/>Equipment availability, prices and specifications are subject to change without notice.</div> |                                                                                                                                                                                                                                                                                                                                                                              |