

# HALE

## TRAILER

### BRAKE & WHEEL



A039249-A039299

VIN: 85995-86045

#### SALES | RENTALS | PARTS | SERVICE

|                   |              |                  |              |
|-------------------|--------------|------------------|--------------|
| Allentown, PA:    | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD:    | 888-601-7500 | Portland, ME:    | 800-325-4253 |
| Concord, NC:      | 800-438-2250 | Raleigh, NC:     | 833-418-9777 |
| Delmar, DE:       | 866-486-1400 | Scranton, PA:    | 800-569-1400 |
| Des Moines, IA:   | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD:       | 800-544-7127 | Voorhees, NJ:    | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA:     | 800-854-5310 |

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

#### Velocity 53' Air Slider (Model Code: HAVSF22SAT)

Order Number: 40052

**Length / Width:** 53 feet x 102 inches

**Suspension Type:** Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

**Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

**Flooring:** 1 1/8 inch wood

**Crossmembers:** 12 inch centers - 4 inch jr. I-steel

**Side Rails:** 6 inch structural channel @ 6.5 lbs/ft

**Stake Pockets:** 3/16 inch steel on 24 inch centers

**Pipe Spools:** Double between stake pockets

**Rubrail:** 3/8 inch x 2 1/2 inch steel

**Main Beams:** 130K load bearing flanges

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM Standard with Forward & Rear Bracing

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkheads:** Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high for use with front pockets

**Bulkhead Pockets:** 4 - F-5 DOT-type steel

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks; Dust Shields, Aluminum Air Tanks

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 2S/1M - no cable or tool

**Axle Spread:** 49 inches (C/L kingpin to C/L rear axle in front position is 40 feet or less)

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

**Tires:** 11R 22.5 14PR OEM standard tires

**Tire Inflation System:** None standard

**Suspension Detail:** Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump :** Installed

**Front Corners:** Tapered

**Electrical System:** LED: 5 lights/side, 3 lights/side on rear

**Paint:** Black urethane with Velocity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed on rubrails

**Bumper:** Weld-on type - meets underide requirements

**Mudflaps:** 1 set OEM standard behind rear axle

**Spare Tire Carrier:** None standard

**Winch Track:** Steel on road side

**Sliding Winches:** 15 Zinc Winches 8 R/S & 7 C/S

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

**Unit Numbers & Decals:** Not installed

Estimated Weight (lbs) (+/- 3%)

13,053

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.