HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A039459-A039482

VIN: S038116-S038139

Infinity Drop Deck 48' Wide Spread Air (Model Code: HAICD12WSA)

Length / Width: 48 feet x 102 inches

Suspension Type: Wide spread air — **Estimated Weight (lbs) (+/- 3%)** **10,335**

Deck Lengths: 10 feet front and 38 feet rear

Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded

Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: NONE INSTALLED

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges; Approximately 1 Inch Camber (+/- 1")

Kingpin: 18 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: No Front Bulkhead Pockets Or Inside Reinforcements

Bulkheads: None standard

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 255/70R 22.5 16PR OEM MID-GRADE BRAND GENERAL HT+

Tire Inflation System: None standard

Suspension Detail: AANL23K Intraax air ride

Auto Glad Hand Dump : No Auto Glad Hand Dump

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None Standard

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets underride requirements - painted steel

Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle

Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD

Sliding Winches: NO SLIDING WINCHES or Rope Hook/ Winch Strap Hook Retainers Installed

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.