



Hale Trailer Brake & Wheel

Front Pin-On Axle 039693

Steerable Dolly 039694

Rear Pin-On Axle 039695

TKPA1 Flip Axle (FRONT PIN-ON AXLE)

10988-TKFA1

10988 - STANDARD EQUIPMENT

Pan style design

Air ride suspension

Automatic slack adjusters

8.25 x 22.5 10-hole disc wheel

One-piece axle seals

Pro tork axle nuts

LED lights, 50 state legal

Electrical system per DOT regulations

Flagholders

Rubber mounted sealed lights with sealed harness system

Mudflaps

Red and white conspicuity markings

Paint: Trail King 2-part polyurethane

Item #	Category	Description	Weight (lbs)	Qty
62831	Open Deck	TKPA1 Flip Axle (FRONT PIN-ON AXLE) <i>Identical to D1921 lift brackets (2) d-rings on front face Includes Gn support plate</i>		
10990	Axle Spacing	60" axle spacing		
9998	Overall Width	Alternative Option Selected. See Add'l Options Section Below.		
10993	Beam Depth	For correct Flip Axle beam depth, specify the Serial # of the corresponding trailer. <i>Goes with 120LPSD</i>		
10995	Position	Front flip axle		
	Flip Axle Styles	Alternative Option Selected. See Add'l Options Section Below.		
11004	Upper Bracket Style	Upper Links for trailers other than HDG ADV Plus		
11007	Axles	27,000 lb (3/4" wall) axle		

9998	Brakes	Alternative Option Selected. See Add'l Options Section Below.	
11008	Hub / Drum	Steel hub-piloted - Cast drum	
08182	Wheel Finish (inside)	Steel wheels (per wheel)	2
08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)	2
08134	Tire Size	235/75R17.5 - 16 ply in lieu of STD 255/70R22.5 - 16 ply (per tire)	4
9998	Lights / Electrical	Alternative Option Selected. See Add'l Options Section Below.	
08024	Paint	Black S7203 with white decals (735-432-039)	

10988-Front Pin-On

Item #	Category	Description	Weight (lbs)	Qty
60690	Custom Options	#60690 TKFA1 Flip Axle 10' wide		
61376	Custom Options	#61376 TKFA1 6.75 x 17.5 8-hole disc wheels		
71222	Custom Options	71222 TKFA1 - Non Load Bearing, 11ga smooth Steel Wheel Cover on flip.		

TKPA1 Flip Axle (REAR PIN-ON AXLE)

10988-TKFA1

10988 - STANDARD EQUIPMENT	Electrical system per DOT regulations
Pan style design	Flag holders
Air ride suspension	Rubber mounted sealed lights with sealed harness system
Automatic slack adjusters	Mudflaps
8.25 x 22.5 10-hole disc wheel	Red and white conspicuity markings
One-piece axle seals	Paint: Trail King 2-part polyurethane
Pro tork axle nuts	
LED lights, 50 state legal	

Item #	Category	Description	Weight (lbs)	Qty
62831	Open Deck	TKPA1 Flip Axle (REAR PIN-ON AXLE) <i>Identical to D1922 lift brackets</i>		

10990	Axle Spacing	60" axle spacing	
9998	Overall Width	Alternative Option Selected. See Add'l Options Section Below.	
10993	Beam Depth	For correct Flip Axle beam depth, specify the Serial # of the corresponding trailer. <i>Goes with 120LPSD</i>	
10995	Position	Rear flip axle <i>Delete D-rings from rear channel (there is no rear channel on this unit)</i>	
9998	Flip Axle Styles	Alternative Option Selected. See Add'l Options Section Below.	
09998	Upper Bracket Style	Alternative Option Selected. See Add'l Options Section Below.	
11007	Axles	27,000 lb (3/4" wall) axle	
9998	Brakes	Alternative Option Selected. See Add'l Options Section Below.	
11008	Hub / Drum	Steel hub-piloted - Cast drum	
08182	Wheel Finish (inside)	Steel wheels (per wheel)	2
08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)	2
08134	Tire Size	235/75R17.5 - 16 ply in lieu of STD 255/70R22.5 - 16 ply (per tire)	4
9998	Lights / Electrical	Alternative Option Selected. See Add'l Options Section Below.	
08024	Paint	Black S7203 with white decals (735-432-039)	

10988-Rear Pin-On

Item #	Category	Description	Weight (lbs)	Qty
60690	Custom Options	#60690 TKFA1 Flip Axle 10' wide		
61376	Custom Options	#61376 TKFA1 6.75 x 17.5 8-hole disc wheels		
72008	Misc info	72008 TKPA1 - Brackets at rear for push/tow bar. Axles being used as pin-on for LPSD		

TK120LPSD

Item #	Category	Description	Weight (lbs)	Qty
61830	Custom Options	TK120LPSD 6 Axle, Rear Steering Dolly (Identical to D9568) <i>10' wide (24) 235/75R 17.5 tires 60" axle spacing (16'-1" spread between axle groups) Air raise and lower valve 24HP honda SCU Auto or remote manual steering 8" lift hydraulic hat box push/tow bar at rear Aux air outlet for power tools chain up's for front axle group power beyond for hydraulics wide load sign brackets at rear 36" by 10' rotating platform with (4) d-rings Flag holders front and rear Brackets for oversized load sign on tow bar</i>		
62537	Custom Options	#62537 - Fenders on dolly, front axle group		
62536	Custom Options	#62536 - Pivoting jack w/wheel on tow bar		
62831	Custom Options	#62831 - Pin-on front and rear axles ilo std 6 fixed axles		
08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)		8
62033	Custom Options	#62033,TK120LPSD, Wireless remote for steering and hydraulic hatbox (4B/2F)		
08024	Paint	Black S7203 with white decals (735-432-039)		
08182	Wheel Finish (inside)	Steel wheels (per wheel)		8

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.