

HALE

TRAILER

BRAKE & WHEEL

Hale Trailer Brake & Wheel

040691-040693

Talbert Manufacturing, Inc.

Model: AC-20-AR

Capacity in tons: 20

1. TONGUE

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks
Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle Seven pin connector

Headboard 8" high full width

2. DECK

Deck section design One piece tongue, main beam and beavertail (cold formed)

Deck section length 27'-0" (21'-0" flat with 6'-0" beavertail)

Deck section width 8'-6"

Loaded deck height 32-1/4"

Flooring 1-1/2" apitong

Lash rings 10 total -

Crossmembers 6" deep hi-tensile

Mainbeams 12" deep hi-tensile

Sidemembers 8" deep hi-tensile

Beavertail 6'-0" with wood flooring full width

Ramps 38" wide x 6'-0" long air ramps with wood flooring, stored vertically with lock bar

3. RUNNING GEAR

Number of axles 2

Axle capacity 25,000#, full width track

Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5)

Tires Eight (8) 215/75R17.5 (H) 16PR radials

Suspension Use valve stem extensions on inside wheels

44,800# Hutch spring

4. GENERAL

Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint Valspar standard Talbert black

Estimated empty weight 9,140#

Additional general specifications Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.