HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A041270-A041294

VIN: S039872-S039896

Infinity Flat 48' Air Slider (Model Code: HAICF12SAT)	Order Number: 40312
Length / Width: 48 feet x 102 inches	
Suspension Type: Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Single Coil Hauling Package: Included	
Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact	
Chain Cargo Tie Downs: None included	
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
Rubrail: Integrated with siderail	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard with Forward & Rear Bracing	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front	
Bulkheads: Removable Galvanized Steel 4 post NON-DOT bulkhead - no turnback - 48 inches high for use with front pockets	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks, Aluminum Air Tank	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 2S/1M - no cable or tool	
Axle Spread: 49 inches	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 11R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable	
Air Assist Slide Box Pins: Standard mount of controls on slider frame	
Auto Glad Hand Dump : Installed	
Front Corners: Tapered steel	
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD	
Paint: Black urethane on steel parts with Infinity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Weld-on type - meets underride requirements - painted steel	
Mudflaps: 1 set OEM standard behind rear axle	
Spare Tire Carrier: None standard	
Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD	
Sliding Winches: 15 Zinc Finished Winches: (8) R/S & (7) C/S; each side with Sliding Rope Hook/Winch Strap Hook Retainers	
27 foot Winch Straps: None standard	
30 foot Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Install registration holder - OEM standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

Estimated Weight (lbs) (+/- 3%) **10,788**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.