HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	**Little Rock, AR:**	833-424-8944
Baltimore, MD:	888-601-7500	**Portland, ME:**	800-325-4253
Concord, NC:	800-438-2250	**Raleigh, NC**	833-418-9777
Delmar, DE:	866-486-1400	**Scranton, PA:**	800-569-1400
Des Moines, IA:	888-673-5011	**Springfield, MA:**	800-854-5306
Elkton, MD:	800-544-7127	**Voorhees, NJ:**	800-232-6535
Jacksonville, FL:	800-828-3055	**Walpole, MA:**	800-854-5310

haletrailer.com • follow us online **@haletrailer**

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A042069-A042098
VIN: S040665-S040694

Velocity 48' Spring Slider (Model Code: HAVSF12SST)	**Order Number:** 40485
Length / Width: 48 feet x 102 inches	
Suspension Type: Sliding spring tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch wood	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 8.2 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Pipe Spools: Double between stake pockets	
Rubrail: 3/8 inch x 2 1/2 inch steel	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard with Forward & Rear Bracing	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkheads: Removable Galvanized Steel 4 post NON-DOT bulkhead - no turnback - 48 inches high for use with front pockets	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks, aluminum air tank	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 2S/1M - no cable or tool	
Axle Spread: 49 inches	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Oil in hubs	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 11R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: OEM Standard 3-leaf spring slider - 60 inches adjustable	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD	
Paint: Black urethane with Velocity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed on rubrails	
Bumper: Weld-on type - meets underride requirements	
Mudflaps: 1 set OEM standard behind rear axle	
Spare Tire Carrier: None standard	
Winch Track: Steel on road side	
Sliding Winches: 12 zinc winches	
27 foot Winch Straps: None standard	
30 foot Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Install registration holder - OEM standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

Estimated Weight (lbs) (+/- 3%) **12,418**

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.