HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

TRAIL KING industries

A042136-A042143
VIN: Z3110-Z3117

TKHB1 Hydraulic Booster

11745-HB1_New

STANDARD EQUIPMENT
Rubber mounted sealed lights and sealed harness system
Electrical system per ICC/DOT regulations
Red & white conspicuity markings

11745-Base

Item #	Category	Description	Weight (lbs)	Qty
11745	Open Deck	TKHB1 Hydraulic Booster		

11745-General - TKHB1

Item #	Category	Description	Weight (lbs)	Qty
11748	Overall Width	102" overall width		
17714	Beam Depth	For correct beam depth, specify the Serial # of the corresponding trailer.		
15635	Landing Gear	Drop-leg jack		
08024	Paint	S7203 Black with white decals		
17866	Paint	Zinc-rich Primer		
18508	Paint	Red & white conspicuity markings		
15772	Flagholders	Flag Holders		

11745-Suspension - TKHB1

Item #	Category	Description	Weight (lbs)	Qty
14672	Suspensions / Axles	Air ride suspension		
14642	Suspensions / Axles	Raising/lowering air control panel (includes liquid filled air gauge)		
15639	Suspensions / Axles	Dump valve		
15640	Suspensions / Axles	27,000-lb (3/4" wall) axle with chain ups (per complete axle)		
18721	Suspensions / Axles	Wheel end lube type - Semi-fluid grease		
11793	Axle Spacing	14' 1" axle spacing from center of the last axle on the trailer to the first axle on the booster		
O9998	Brakes	See Custom Option Below.		
11795	Brakes	2S1M Anti-Lock Brake System with Service Air Chambers		
14138	Hub / Drum	Steel hub piloted, Cast drum, Tapered (D) spindle (per complete axle)		
O9998	Wheels (inside)	See Custom Option Below. *Machine finish aluminum 17.5*		2
O9998	Wheels (outside)	See Custom Option Below. *Machine Finish Aluminum*		2
O9998	Tires	See Custom Option Below.		
14759	Flaps, Mud Guards & Fenders	Mudflaps		
15775	Suspensions / Axles	TireMaax Pro tire inflation system (1 Axle)		
O9999-01	Custom Options	Custom Option 203430 - TKHB1, TKHB1+1, TKHB2, TKHB2+1: Low-profile booster to work with trailer that has axles through the frame		
O9999-03	Custom Options	Custom Option 200800 - General: 245/70R x 17.5 Tires with 6.75 x 17.5 8-Hole Steel Disc Wheels and 12.25" x 7.5" Drum Brakes ILO 275/70R x 22.5 - Per Axle		

O9999-04	Custom Options	Custom Option 208950 - General: Axle to be equipped w/ HXL5 wheel ends ILO std. (per axle) - (Requires semi-fluid grease & 102" OAL trailer		

11745-Miscellaneous - TKHB1

Item #	Category	Description	Weight (lbs)	Qty
15636	Tie Downs	Lifting eye and Straight D-rings for loading		
11815	Miscellaneous	5 ½ HP self-contained unit		
14666	Miscellaneous	Remote pivot bearing lube kit		
14765	Miscellaneous	Wide load sign brackets		
15629	Miscellaneous	5-gallon nitrogen accumulator		

11745-Electrical - TKHB1

Item #	Category	Description	Weight (lbs)	Qty
15768	Lights / Electrical	3rd tail light package plus additional 4" round quad flash amber strobes at rear with switch		
14648	Lights / Electrical	Grote LED Lights		
15765	Lights / Electrical	Side marker lights and (3) ID lights on tail channel. Light type to match all trailer components		
18230	Lights / Electrical	Center identification lights illuminated for marker lights		
18726	Lights / Electrical	Grote sealed electrical harness system		

Item #	Category	Description	Weight (lbs)	Qty
210095	Custom Options	Custom Option Model TK110ES TRAILER? 52’-11” Overall Length? 8’-6’’ Overall width (to outside of d-ring brackets) 9’-6” narrow gooseneck (1 KP setting, 16” w/ 78” swing) 48” flip gooseneck extension (2 KP settings, 16” and 30” w/126 and 112” swing) 5th wheel height to be adjustable per option 73575 (49” and 58”) 31” deck height (axles through the frame) 43’-5” lower deck (67’ max extended) Reinforced for single axle hydraulic booster (3) axles ¾” wall Air ride suspension w/ raising and lowering 54” axle spacing 245/70R17.5 radial tires 6.75 X 17.5 machined finish aluminum wheels 12.25 X 7.5 drum brakes 7” mill side channel Aluminum decking with 1-1/8” apitong nailer (outer bays main deck) 10 GA. smooth MF80 steel (inner bays main deck and wheel area where required) Delete decking on wheel area where not required. 2 speed landing gear 5 pair d-rings main deck 1 pair d-rings 12” behind first pair on deck 2 pair d-rings on bolster ahead of 1st axle 1 d-ring on each remaining bolster 1 pair d-rings on tail channel 1 pair d-rings on rear of GN 12” above deck 4 – pole female electrical socket wired to clearance light in tail channel 1 pair 4” amber strobes at rear with on /off switch 2 pair 1’ round flag holders (1 at front of deck and 1 on tail channel) Brackets only for removable oversize load sign “Caution Wide Turn” mud flaps LED lights Electrical system per DOT regulations Registration holder Red & white conspicuity markings Ref. Drawing 73314B		
O9999-02	Custom Options	Custom Option 208950 - General: Axle to be equipped w/ HXL5 wheel ends ILO std. (per axle) - (Requires semi-fluid grease & 102" OAL trailer) *ILO ATS axle ends*		3
O9999-03	Custom Options	Custom Option TireMaax Pro tire inflation system (3 Axle) ++		
O9999-03	Custom Options	Custom Option 245/70R 17.5 Tires		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.