HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE TRAILER

A042254-A042257

VIN: A8498-A8501

Renegade XN20 Extendable Deck,Air Tandem, 20 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE XN20)	
RENLXT40NF*829542	**Quote Number:** 3015918
	Est. Wt.: 22,705# +/- 3%
TRAILER - GENERAL	
Capacity: 40 tons in 16-foot length - GAWR and GVWR determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck when deck is fully closed. Note: Only rigid self supporting loads when deck is open. The load base becomes the open deck minus 2ft.	
Length (Trailer Only): 50 feet 1 inch (closed); 71 feet 1 inch (open)	
Width: 8 feet 6 inches	
Compatibility: Designed to accept optional third flip axle	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Power Source: None	
DECK	
Deck Design: Flat level telescopic deck design	
Deck Length: 29 feet 0 inches clear deck length (retracted) - 50 feet 0 inches (extended)	
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: None	
Crossmembers: On 24 inch centers	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Deck to Bogie Connection: Fixed	
AXLES	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches spread (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields: None	
Spring Brakes: Spring brakes on 2 axles	
SUSPENSION	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride with automatic controls	
First Axle Lift: Chain lift included on first axle when 34ft deck is selected	
ABS: 4S/2M system without diagnostic tool and cable	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 LvL One buffed outside/steel inside - hub-piloted	
Tires: 255/70R 22.5 H ply OEM Standard	
Hubodometer: None Standard	

Tire Inflation: Tire Inflation Prepped Only	
REAR BRIDGE	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 41 inches	
Bumper: 3 tail light package	
Mini Boom Trough & Traction Cleats: Mini boom trough and traction cleats installed on sloped bogie ramp	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Liquid Filled Gauge: Included	
Accent Package: Stainless steel bumper insert	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 8 marker lights per side including mid-turn	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 12 pair - 24 total	
Flag Holders: 2 pair flag holders	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.